

LAB/ADMIN BUILDING - LAB SPACE CONSTRUCTION PHASING REQUIREMENTS:

THE LAB/ADMIN BUILDING INCLUDES TWO LABORATORY SPACES (LABORATORY 1 - 101 AND LABORATORY 2 - 102). KITSAP COUNTY REQUIRES FULL USE OF AT LEAST ONE LABORATORY SPACE THROUGHOUT THE ENTIRE CONSTRUCTION PROCESS. FULL USE IS DEFINED AS THE FOLLOWING:

- FULLY FUNCTIONAL HVAC SYSTEM FOR SPACE CONDITIONING AND VENTILATION.
- FULLY FUNCTIONAL SPACE LIGHTING.
- TWO FULLY FUNCTIONAL COUNTERTOP MOUNTED OVENS (EXISTING EQUIPMENT).
- ONE FULLY FUNCTIONAL COUNTERTOP MOUNTED AUTOCLAVE (EXISTING EQUIPMENT).
- ONE FULLY FUNCTIONAL FUME HOOD AND ASSOCIATED EXHAUST FAN (EXISTING EQUIPMENT).
- UNOBSTRUCTED ACCESS FROM THE BUILDING EXTERIOR.

LAB/ADMIN BUILDING - LAB SPACE SUGGESTED PHASING PLAN:

THE CONTRACTOR SHALL PROVIDE A PHASING PLAN FOR ALL SCOPE RELATED TO THE LAB/ADMIN BUILDING TO THE DEPARTMENT OF COMMUNITY DEVELOPMENT (DCD) WHEN APPLYING FOR APPLICABLE PERMITS ASSOCIATED WITH THIS PROJECT.

PHASE 1: LABORATORY 1 - 101 REMAINS FULLY FUNCTIONAL. ALL EXISTING EQUIPMENT SERVING THIS SPACE IS FULLY FUNCTIONAL. PERFORM DEMOLITION SCOPE WITHIN LABORATORY 2 - 102. PERFORM NEW CONSTRUCTION WORK IN LABORATORY 2 - 102. COMPLETE TAB AND CX FOR ALL HVAC EQUIPMENT SERVING LABORATORY 2 - 102. THE COUNTY SHALL RELOCATE TWO OVENS (EXISTING EQUIPMENT) AND ONE AUTOCLAVE (EXISTING EQUIPMENT) FROM LABORATORY 1 - 101 TO LABORATORY 2 - 102. LABORATORY 2 - 102 BECOMES FULLY FUNCTIONAL.

PHASE 2: PERFORM DEMOLITION SCOPE WITHIN LABORATORY 1 - 101. PERFORM NEW CONSTRUCTION WORK IN LABORATORY 1 - 101. COMPLETE TAB AND CX FOR ALL HVAC EQUIPMENT SERVING LABORATORY 1 - 101. LABORATORY 1 - 101 BECOMES FULLY FUNCTIONAL. THE COUNTY SHALL RELOCATE EXISTING EQUIPMENT AS NEEDED BETWEEN THE TWO LAB SPACES.

Issued for Construction




KITSAP COUNTY

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC SYSTEM REPLACEMENT

JUNE 2025


LOCATION MAPS

NTS



VICINITY MAP

NTS



COUNTY COMMISSIONERS

Christine Rolfs - District #1

Oran Root - District #2

Katherine T. Walters - District #3

APPROVED BY

1/21/2026

DATE

KORY ANGLESEY, P.E.
DIRECTOR OF PUBLIC WORKS

1/20/2026

DATE

CHRISTOPHER PIERCY
ASST DIRECTOR OF PUBLIC WORKS - UTILITIES

PREPARED BY



IN ASSOCIATION WITH

Mechanical Engineer	- FSi Engineers
Architect	- Rolluda Architects
Structural Engineer	- BHC Consultants, LLC
Electrical Engineer	- FSi Engineers (Lab/Admin Building & Headworks Building) - BHC (Process Building)

LAB/ADMIN BUILDING – LAB SPACE CONSTRUCTION PHASING REQUIREMENTS:

THE LAB/ADMIN BUILDING INCLUDES TWO LABORATORY SPACES (LABORATORY 1 – 101 AND LABORATORY 2 – 102). KITSAP COUNTY REQUIRES FULL USE OF AT LEAST ONE LABORATORY SPACE THROUGHOUT THE ENTIRE CONSTRUCTION PROCESS. FULL USE IS DEFINED AS THE FOLLOWING:

- FULLY FUNCTIONAL (OR AS-IS) SPACE CONDITIONING AND VENTILATION.
- FULLY FUNCTIONAL SPACE LIGHTING.
- FULLY FUNCTIONAL ELECTRICITY AND HOT WATER.
- UNOBSTRUCTED ACCESS FROM THE BUILDING EXTERIOR AND TO/FROM INTERIOR RESTROOMS.

LAB/ADMIN BUILDING – LAB SPACE SUGGESTED PHASING PLAN:

THE CONTRACTOR SHALL PROVIDE A PHASING PLAN FOR ALL SCOPE RELATED TO THE LAB/ADMIN BUILDING TO THE DEPARTMENT OF COMMUNITY DEVELOPMENT (DCD) WHEN APPLYING FOR APPLICABLE PERMITS ASSOCIATED WITH THIS PROJECT.

PHASE 1: LAB 1-101 REMAINS FULLY OPERATIONAL, WITH ALL EXISTING EQUIPMENT IN PLACE AND FUNCTIONING (MAINTAIN HOT WATER SUPPLY PIPING TO THIS SPACE THROUGHOUT PHASE 1.) CONTRACTOR COMPLETES DEMOLITION AND CONSTRUCTION IN LAB 2-102, MECHANICAL ROOM 108, AND GENERAL OFFICE 104, THEN COMPLETES TAB AND COMMISSIONING FOR HVAC SYSTEMS SERVING THESE AREAS PRIOR TO OCCUPANCY.

PHASE 2: COUNTY RELOCATES EQUIPMENT FROM LAB 1-101 TO LAB 2-102 (1-2 WORKDAYS). CONTRACTOR COMPLETES DEMOLITION AND CONSTRUCTION IN LAB 1-101 AND THEN COMPLETES TAB AND COMMISSIONING FOR HVAC SYSTEMS SERVING LAB 1-101.

PROJECT SITE INFO

OWNER: KITSAP COUNTY DEPARTMENT OF PUBLIC WORKS/WASTEWATER
614 DIVISION STREET, PORT ORCHARD, WASHINGTON 98366
(206)337-5777

DESIGN MECHANICAL ENGINEER:
FSI ENGINEERS
PIER 54
1001 ALASKAN WY SUITE 200
SEATTLE, WA 98104
(206)622-3321

DESIGN ARCHITECT:
ROLLUDA ARCHITECTS
105 SOUTH MAIN ST SUITE 4S
SEATTLE, WA 98104
(206)624-4222

DESIGN STRUCTURAL ENGINEER:
BHC CONSULTANTS, LLC
950 PACIFIC AVE
TACOMA, WA 98402
(206)505-3400

DESIGN ELECTRICAL ENGINEERS:
FSI ENGINEERS INC. – LAB/ADMIN BUILDING & HEADWORKS
PIER 54
1001 ALASKAN WY SUITE 200
SEATTLE, WA 98104
(206)622-3321

BHC CONSULTANTS, LLC – PROCESS BUILDING
950 PACIFIC AVE
TACOMA, WA 98402
(206)505-3400

DRAWING INDEX

G0.00 COVER SHEET, LOCATION AND VICINITY MAPS AND MASTER SITE PLAN
G0.01 DRAWING INDEX

A1.01 LAB-ADMIN BUILDING FLOOR PLAN
A1.02 LAB-ADMIN BUILDING ROOF PLAN
A1.03 LAB-ADMIN REFLECTED CEILING PLAN
A1.04 LAB-ADMIN BUILDING ELEVATIONS
A1.05 LAB-ADMIN BUILDING ELEVATIONS
A1.06 LAB-ADMIN BUILDING SECTIONS
A1.07 LAB-ADMIN BUILDING SECTIONS
A1.08 LAB-ADMIN WALL SECTIONS
A1.09 LAB-ADMIN DOOR & WINDOW SCHEDULES
A1.10 LAB-ADMIN SKYLIGHT DETAILS
A1.11 LAB-ADMIN BUILDING CEILING DETAILS
A1.12 LAB-ADMIN TYPICAL PENETRATIONS DETAILS


S0.01 STRUCTURAL GENERAL NOTES
S1.01 ADMINISTRATION BUILDING ROOF PLAN AND DETAIL
S2.01 ADMINISTRATION BUILDING SKYLIGHT SUPPORT SECTIONS AND DETAILS

M0.01 HVAC LEGEND, ABBREVIATIONS AND GENERAL NOTES
M0.02 WSEC COMPLIANCE FORMS
M0.03 LAB-ADMIN BUILDING – HVAC DEMOLITION FLOOR PLAN
M1.01 LAB-ADMIN BUILDING – HVAC FLOOR PLAN
M4.01 LAB-ADMIN BUILDING – HVAC ENLARGED PLANS
M4.02 LAB-ADMIN BUILDING – HVAC SECTIONS
M4.03 LAB-ADMIN BUILDING – HVAC SECTIONS
M4.04 LAB-ADMIN BUILDING – HVAC SECTIONS
M5.01 HVAC SCHEDULES
M6.01 SEQUENCE OF OPERATIONS AND POINTS LIST
M7.01 PROCESS BUILDING – HVAC FLOOR PLAN
M8.01 HEADWORKS BUILDING – HVAC ROOF PLAN

E0.00 ELECTRICAL LEGEND AND GENERAL NOTES
E0.01 ELECTRICAL ABBREVIATIONS
E0.02 ONE-LINE DIAGRAM – ADMINISTRATIVE AND LABORATORY BUILDING
E0.03 POWER – SITE LAYOUT – ADMINISTRATIVE AND LABORATORY BUILDING
E0.04 POWER – DEMOLITION – ADMINISTRATIVE AND LABORATORY BUILDING – LEVEL 1
E1.01 POWER – ADMINISTRATIVE AND LABORATORY BUILDING – LEVEL 1
E2.01 LIGHTING – ADMINISTRATIVE AND LABORATORY BUILDING – LEVEL 1
E3.01 POWER – PROCESS BUILDING – LEVEL 1
E3.02 POWER – PROCESS BUILDING – LEVEL 2
E4.01 ELECTRICAL DETAILS – ADMINISTRATIVE AND LABORATORY BUILDING
E5.01 ELECTRICAL SCHEDULES – ADMINISTRATIVE AND LABORATORY BUILDING
E6.01 ELECTRICAL – PROCESS BUILDING – PNL 7200 HVAC CONTROL PANEL ELEVATION
E6.02 ELECTRICAL – PROCESS BUILDING – PNL 7200 HVAC CONTROL PANEL I/O LISTING
E7.01 ELECTRICAL – PROCESS BUILDING – SCHEMATIC WIRING DIAGRAMS
E7.02 ELECTRICAL – PROCESS BUILDING – SCHEMATIC WIRING DIAGRAMS
E7.03 ELECTRICAL – PROCESS BUILDING – SCHEMATIC WIRING DIAGRAMS
E7.04 ELECTRICAL – PROCESS BUILDING – SCHEMATIC WIRING DIAGRAMS
E7.05 ELECTRICAL – PROCESS BUILDING – SCHEMATIC WIRING DIAGRAMS

Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE



No.	Revision	Date	By	App'd



Seattle // Spokane // Baltimore
Copyright © FSI consulting engineers

Designed: MSS

Scale:

N/A

Drawn: WHB

One Inch at Full Scale

If Not One Inch
Scale Accordingly

Checked:



Kitsap County Public Works
18 57
614 Division Street, MS 26
Port Orchard, WA 98366


CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES

DRAWING INDEX


Drawing: G0.01
Sheet: 2 of 47
File: COMPLETE
Date: September 2025

CONSTRUCTION NOTES


-  1 DEMOLISH EXISTING WINDOW
-  2 EXISTING WINDOW TO REMAIN
-  3 DEMOLISH EXISTING DOOR,
EXISTING FRAME TO REMAIN
-  4 DEMOLISH EXISTING DOOR & FRAME



GENERAL LEGEND

-  NORTH ARROW
-  DETAIL/DRAWING REFERENCE
-  SECTION REFERENCE
-  CONSTRUCTION NOTE
-  REVISION SYMBOL
-  POINT OF CONNECTION

PLAN SYMBOLS



**Call 48 Hours
before You Dig**



No.	Revision	Date	By	Ap



Seattle // Spokane // Baltimore
Copyright © FSi consulting engineers

rolludaarchitects
architecture **planning** interior design

105 S. Main St. Seattle, WA 98104
p. 206.624.4222 f. 206.624.4226
www.rolludaarchitects.com

Designed: MP	Scale
Drawn: AD	Or
Checked: DS	S



KITSAP COUNTY
 **Kitsap County Public Works**
614 Division Street, MS 26

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES


LAB-ADMIN BUILDING FLOOR PLAN

rawing: **A1.01**
heet: 3 of 47
ile: COMPLETE
ate: September 2025


CONSTRUCTION NOTES



DEMOLISH EXISTING SKYLIGHT AND
2X FRAMING





Call 48 Hours
Before You Dig
1-800-424-5555
UNDERGROUND SERVICE



N 1 LAB ADMIN BUILDING - ROOF PLAN

SCALE: 1/4" = 1'-0"



1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184


185

186

CONSTRUCTION NOTES



DEMOLISH EXISTING SKYLIGHT AND
2X FRAMING



1 LAB ADMIN BUILDING - REFLECTED CEILING PLAN

SCALE: 1/4" = 1'-0"

No.	Revision	Date	By App'd

fsi
ENGINEERS
Seattle // Spokane // Baltimore
Copyright © FSI consulting engineers

rolludaarchitects
architecture planning interior design

105 S. Main St. Seattle, WA 98104
p. 206.624.4222 f. 206.624.4226
www.rolludaarchitects.com


Designed: MP
Scale: As indicated
Drawn: AD
One Inch at Full Scale
If Not One Inch
Scale Accordingly
Checked: DS



Kitsap County Public Works
614 Division Street, MS 26
Port Orchard, WA 98366


**CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES
LAB-ADMIN BUILDING REFLECTED
CEILING PLAN**

Drawing: **A1.03**
Sheet: **5** of **47**
File: **COMPLETE**
Date: **September 2025**




Call 48 Hours
Before You Dig
1-800-424-5555
UNDERGROUND SERVICE

0 2' 4' 8' 12'
SCALE: 1/4" = 1'-0"



Call 48 Hours
Before You Dig
1-800-424-5555
UNDERGROUND SERVICE




No.	Revision	Date	By	App'd



rolluda architects
architecture planning interior design

105 S. Main St. Seattle, WA 98104
p. 206.624.4222 f. 206.624.4226
www.rolludaarchitects.com

Designed: MP	Scale: 1/4" = 1'-0"
Drawn: AD	One Inch at Full Scale
Checked: DS	If Not One Inch Scale Accordingly





Kitsap County Public Works
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPDATES
LAB-ADMIN BUILDING ELEVATIONS

Drawing: A1.04
Sheet: 6 of 47
File: COMPLETE
Date: September 2025


0 2' 4' 8' 12'
SCALE: 1/4" = 1'-0"



0 2' 4' 8' 12'

SCALE: 1/4" = 1'-0"

Call 48 Hours
Before You Dig
1-800-424-5555
UNDERGROUND SERVICE



No.	Revision	Date	By	App'd



rolluda architects
architecture planning interior design

105 S. Main St. Seattle, WA 98104
p. 206.624.4222 f. 206.624.4226
www.rolludaarchitects.com



Designed: MP	Scale: 1/4" = 1'-0"
Drawn: AD	
Checked: DS	One Inch at Full Scale If Not One Inch Scale Accordingly





Kitsap County Public Works
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPDATES
LAB-ADMIN BUILDING ELEVATIONS

Drawing: A1.05
Sheet: 7 of 47
File: COMPLETE
Date: September 2025




No.	Revision	Date	By	App'd



Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE



No.	Revision	Date	By	App'd



rolludaarchitects
architecture planning interior design

105 S. Main St. Seattle, WA 98104
p. 206.624.4222 f. 206.624.4226
www.rolludaarchitects.com


Designed: MP	Scale: 1/4" = 1'-0"
Drawn: AD	
Checked: DS	



Kitsap County Public Works
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPDATES
LAB-ADMIN BUILDING SECTIONS

Drawing: A1.07
Sheet: 9 of 47
File: COMPLETE
Date: September 2025



Call 48 Hours
Before You Dig
1-800-424-5555
UNDERGROUND SERVICE

6250
REGISTERED
ARCHITECT
Alex E. Rolluda
STATE OF WASHINGTON

0 1' 2' 4' 6'
SCALE: 1/2" = 1'-0"

No.	Revision	Date	By App'd

fsi
ENGINEERS
Seattle // Spokane // Baltimore
Copyright © FSi consulting engineers

rolluda architects
architecture planning interior design

105 S. Main St. Seattle, WA 98104
p. 206.624.4222 f. 206.624.4226
www.rolludaarchitects.com

Designed: MP
Scale: 1/2" = 1'-0"
Drawn: AD
One Inch at Full Scale
If Not One Inch
Scale Accordingly
Checked: DS




Kitsap County Public Works
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES
LAB-ADMIN BUILDING WALL SECTIONS

Drawing: A1.08
Sheet: 10 of 47
File: COMPLETE
Date: September 2025


MARK	DOOR						TYPE	FRAME MATERIAL	FINISH	HARDWARE SET	FIRE RATING	DETAILS			COMMENTS	
	WIDTH	HEIGHT	THICKNESS	TYPE	MATERIAL	FINISH						HEAD	JAMB	SILL		
101	6'-0"	7'-0"	1 3/4"	A	HM	PT	ITG	EXISTING	HM	PT	01 (SEE SPECS)		EXISTING	EXISTING	EXISTING	ASTRAGAL, CLOSER (VERIFY & MATCH EXISTING DOOR SIZE)
102	6'-0"	7'-0"	1 3/4"	A	HM	PT	ITG	EXISTING	HM	PT	01 (SEE SPECS)	-	EXISTING	EXISTING	EXISTING	ASTRAGAL, CLOSER (VERIFY & MATCH EXISTING DOOR SIZE)
103	5'-0"	7'-0"	1 3/4"	B	HM	PT	-	1	HM	PT	01 (SEE SPECS)	2 HR	A6.01 / 3	A6.01 / 4	A6.01 / 5	VERIFY & MATCH EXISTING DOOR OPENING SIZE

DOOR TYPE



1 DOOR & FRAME TYPES

SCALE: 1/4" = 1'-0"



3 EXTERIOR DOOR HEADER

SCALE: 3" = 1'-0"


FRAME TYPE

MARK	TYPE	WINDOW				DETAILS			COMMENTS
		FRAME MATERIAL	GLAZING	WIDTH	HEIGHT	SILL HEIGHT	HEAD	JAMB	
101	A	ALUM, MFR ANOD	ITG	4'-0"	4'-0"	3'-4"	A6.01 / 6	A6.01 / 7	A6.01 / 8
102	A	ALUM, MFR ANOD	ITG	4'-0"	4'-0"	3'-4"	A6.01 / 6	A6.01 / 7	A6.01 / 8
103	B	ALUM, MFR ANOD	ITG	10'-8"	4'-0"	3'-4"	A6.01 / 6	A6.01 / 7	A6.01 / 8
104	B	ALUM, MFR ANOD	ITG	10'-8"	2'-8"	4'-8"	A6.01 / 6	A6.01 / 7	A6.01 / 8
105	B	ALUM, MFR ANOD	ITG	10'-8"	4'-0"	3'-4"	A6.01 / 6	A6.01 / 7	A6.01 / 8

NOTE: VERIFY AND MATCH EXISTING WINDOW OPENING SIZE

MATERIAL/FINISH LEGEND

ALUM	ALUMINUM
ANOD	ANODIZED
EXT	EXTERIOR
HM	HOLLOW METAL
ITG	INSULATED TEMPERED GLASS
INT	INTERIOR
MFR	MANUFACTURER
PT	PAINTED
SS	STAINLESS STEEL




2 WINDOW TYPES

SCALE: 1/4" = 1'-0"




SCALE: 1/4" = 1'-0"




5 EXTERIOR DOOR SILL

SCALE: 3" = 1'-0"




6 EXTERIOR WINDOW HEADER

SCALE: 3" = 1'-0"



7 EXTERIOR WINDOW JAMB

SCALE: 3" = 1'-0"




8 EXTERIOR WINDOW SILL

SCALE: 3" = 1'-0"



SCALE: 3" = 1'-0"

Call 48 Hours
Before You Dig
1-800-424-5555
UNDERGROUND SERVICE



No.	Revision	Date	By	App'd



Seattle // Spokane // Baltimore

Copyright © FSI consulting engineers

rolludaarchitects
architecture planning interior design

105 S. Main St. Seattle, WA 98104
p. 206.624.4222 f. 206.624.4226
www.rolludaarchitects.com


Designed: MP	Scale: As indicated
Drawn: AD	
Checked: DS	




Kitsap County Public Works
614 Division Street, MS 26
Port Orchard, WA 98366

**CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES
LAB-ADMIN BUILDING DOOR & WINDOW SCHEDULES**


Drawing: A1.09
Sheet: 11 of 47
File: COMPLETE
Date: September 2025




1B SKYLIGHT SECTION - OPTION B



1A SKYLIGHT SECTION - OPTION A




5B SKYLIGHT TO ROOF - OPTION B




6B SKYLIGHT TO RIDGE - OPTION B

No.	Revision	Date	By App'd




1 TYPICAL ACP GRID LAYOUT
SCALE: 1 1/2" = 1'-0"


SEE DETAIL 11 - THIS SHEET FOR WIRE ATTACHMENT TO STRUCTURE



2 ACP CEILING TO WALL - ATTACHED END, TYP.
SCALE: 3" = 1'-0"




3 TYPICAL ACP CEILING BRACING
SCALE: 1 1/2" = 1'-0"



4 ACP CEILING TO WALL - FREE END, TYP.
SCALE: 3" = 1'-0"


5 HANGER WIRE ATTACHMENT, TYP.
SCALE: 3" = 1'-0"

VERTICAL ATTACHMENT




STRUCTURAL FRAMING ABOVE
12 GA METAL ANGLE
MIN 4 TURNS
12 GA HANGER WIRE

SPLAYED ATTACHMENT



STRUCTURAL FRAMING ABOVE
12 GA 1" WIDE X 2" LONG STEEL STRAP
MIN 4 TURNS
12 GA HANGER WIRE

6 ACP COMPRESSION STRUT, TYP.
SCALE: 3" = 1'-0"



CRIMP TOP OF TUBING FLAT & ATTACH WITH (1) 5/16" DRILLED LAG BOLT
STRUCTURAL FRAMING ABOVE
3/4" DIA 14 GA STL TUBING
SECURE TUBE SECTIONS TOGETHER W/SET SCREWS
1/2" DIA 14 GA STL TUBING, CRIMP BOTTOM FLAT AND ATTACH TO MAIN RUNNER WITH (2) #12 SHEET MTL SCREWS, TYP

No.	Revision	Date	By

fsi
ENGINEERS
Seattle // Spokane // Baltimore
Copyright © FSI consulting engineers

rolluda architects
architecture planning interior design
105 S. Main St. Seattle, WA 98104
p. 206.624.4222 f. 206.624.4226
www.rolludaarchitects.com

Designed: MP
Drawn: AD
Checked: DS

Scale: As indicated
One Inch at Full Scale
If Not One Inch Scale Accordingly


 Kitsap County Public Works
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES
LAB-ADMIN BUILDING CEILING DETAILS

Drawing: A1.11
Sheet: 13 of 47
File: COMPLETE
Date: September 2025


Call 48 Hours
Before You Dig
1-800-424-5555
UNDERGROUND SERVICE

6250
REGISTERED
ARCHITECT
Alex E. Rolluda
STATE OF WASHINGTON



1 TYP. INT. WALL PENETRATION DETAIL

SCALE: 3" = 1'-0"



2 TYP. EXT. WALL PENETRATION DETAIL

SCALE: 3" = 1'-0"

0 3" 6" 9" 12"
SCALE: 3" = 1'-0"

Call 48 Hours
Before You Dig
1-800-424-5555
UNDERGROUND SERVICE

6250
REGISTERED
ARCHITECT
Alex E. Rolluda
STATE OF WASHINGTON

No.	Revision	Date	By	App'd

fsi
ENGINEERS
Seattle // Spokane // Baltimore
Copyright © FSI consulting engineers

rolluda architects
architecture planning interior design

105 S. Main St. Seattle, WA 98104
p. 206.624.4222 f. 206.624.4226
www.rolludaarchitects.com

Designed: MP Scale: 3" = 1'-0"
Drawn: AD
One Inch at Full Scale
If Not One Inch
Scale Accordingly
Checked: DS



Kitsap County Public Works
614 Division Street, MS 26
Port Orchard, WA 98366

**CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPDATES
LAB-ADMIN TYPICAL PENETRATION DETAILS**

Drawing: A1.12
Sheet: 14 of 47
File: COMPLETE
Date: September 2025

C:\Users\alvin\Documents\CKWTP_A_Admin Bldg_v2023_alvin636WS.rvt
8/26/2025 4:47:21 PM
COPYRIGHT © 2018 ROLLUDA ARCHITECTS INC

GENERAL STRUCTURAL NOTES

A. GENERAL

- SCOPE
THE GENERAL STRUCTURAL NOTES AND TYPICAL STRUCTURAL DETAILS ARE GENERAL AND APPLY TO THE ENTIRE PROJECT EXCEPT WHERE THERE ARE SPECIFIC INDICATIONS OR MODIFICATIONS TO THE CONTRARY.
- APPLICABLE SPECIFICATIONS AND CODES
ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE BUILDING CODE, (SEE BELOW). THE PROVISIONS OF THE BUILDING CODE SHALL SUPERSEDE THE PLANS AND SPECIFICATIONS EXCEPT WHERE THE PLANS AND SPECIFICATIONS ARE MORE RESTRICTIVE.
- IN ADDITION TO THE BUILDING CODE, CONSTRUCTION SHALL CONFORM TO OTHER STANDARDS AND CODES AS REFERENCED ON THE DRAWINGS OR IN THE SPECIFICATIONS.
- DIMENSIONS
STRUCTURAL DIMENSIONS CONTROLLED BY OR RELATED TO MECHANICAL AND ELECTRICAL EQUIPMENT SHALL BE VERIFIED BY THE CONTRACTOR PRIOR TO CONSTRUCTION.
- REFER TO MECHANICAL AND ELECTRICAL DRAWINGS FOR SIZE AND LOCATION OF ALL OPENINGS FOR DUCTS, PIPING, CONDUITS, ETC., NOT SHOWN. ALL OPENINGS IN STRUCTURAL MEMBERS SHALL BE APPROVED BY THE STRUCTURAL ENGINEER. REFER TO CIVIL DRAWINGS AND SPECIFICATIONS FOR SUBGRADE INFORMATION AND CRITERIA. VERIFY ALL DIMENSIONS WITH CIVIL, MECHANICAL, AND ELECTRICAL DRAWINGS.
- PROVISIONS FOR EQUIPMENT
MECHANICAL AND ELECTRICAL EQUIPMENT SUPPORTS, ANCHORAGES, OPENINGS, PIPE SLEEVES AND, PENETRATIONS, RECESSES AND REVEALS NOT SHOWN ON THE STRUCTURAL DRAWINGS, SHALL BE PROVIDED BY A LICENSED PROFESSIONAL ENGINEER IN THE STATE OF WASHINGTON. SUBMIT FINAL MECHANICAL DESIGN, INCLUDING UNIT WEIGHTS AND ANCHORAGE DESIGN, FOR REVIEW BY ENGINEER OF RECORD.
- CONSTRUCTION LOADS
STRUCTURES HAVE BEEN DESIGNED FOR OPERATIONAL LOADS ON THE COMPLETED STRUCTURES. DURING CONSTRUCTION, THE STRUCTURES SHALL BE PROTECTED BY BRACING AND SUPPORTS WHEREVER EXCESSIVE CONSTRUCTION LOADS MAY OCCUR.
- DRAINAGE SURFACES
SLOPE DRAINAGE SURFACES UNIFORMLY TO DRAIN. SLOPE SHALL BE 1/4" PER FOOT, EXCEPT WHERE NOTED OTHERWISE ON THE PLANS. AT CONTRACTOR'S OPTION, BOTTOM OF SLAB MAY BE LEVEL AND MAINTAIN A MINIMUM THICKNESS AT FLOOR DRAINS.

B. STRUCTURAL DESIGN DATA

- GENERAL
 - BUILDING CODE: 2021 INTERNATIONAL BUILDING CODE WITH KITSAP COUNTY AMENDMENTS AND BY REFERENCE ASCE 7-16 MINIMUM DESIGN LOADS FOR AND BUILDINGS AND OTHER STRUCTURES.
 - OCCUPANCY: U
 - RISK CATEGORY III
 - LOCATION: 47.65° N, 122.63° W, EL 156.45
- DESIGN LOADS
 - DEAD LOAD:
BUILDING STRUCTURE: ACTUAL PLUS 5 PSF COLLATERAL DEAD LOAD ON ROOF SYSTEM
 - LIVE LOAD
BUILDING ROOF: 20 PSF
 - SNOW LOAD
SNOW LOAD IMPORTANCE FACTOR: Is = 1.1
GROUND SNOW LOAD Pg: 25 PSF
SNOW EXPOSURE FACTOR Ce: 0.9
THERMAL FACTOR Ct = 1.0
FLAT-ROOF SNOW LOAD Pf: 17.3 PSF
SLOPING ROOF SNOW LOAD, PS: 25 PSF
 - WIND DESIGN DATA
BASIC WIND SPEED (3 SECOND GUST): 104 MPH
WIND EXPOSURE: B ALL DIRECTIONS
INTERNAL PRESSURE COEFFICIENT: ENCLOSED. GCpi = +/- .18
INTERNAL PRESSURE: ± 7 PSF
 - EARTHQUAKE DESIGN DATA:
NO SEISMIC MASS INCREASE OR MODIFICATION TO THE EXISTING BUILDING STRUCTURE HAS BEEN MADE.

SEISMIC IMPORTANCE FACTOR: Ie = 1.25
SEISMIC DESIGN CATEGORY: D
SITE CLASS D
 $S_s = 1.427$
 $S_i = 0.504$
 $F_v = 1.2$
 $F_v = 1.8$
 $S_{ds} = 1.142$
 $S_{di} = 0.603$

B. STRUCTURAL DESIGN DATA (CONTINUED)

- SOILS DATA:
SOIL BEARING PRESSURE: 1,500 PSF (PRESUMPTIVE)
- CONCRETE
 - DESIGN STRENGTHS
STRUCTURAL CONCRETE: 4000 PSI AT 28 DAYS
PLAIN CONCRETE: 3000 PSI AT 28 DAYS
 - REINFORCEMENT
REINFORCING BARS SHALL BE ASTM A615, GRADE 60, DEFORMED. WELDED WIRE FABRIC SHALL BE ASTM A185 OR A1064, WITH FY = 60 TSI MINIMUM. REINFORCEMENT SHALL BE PLACED, SUPPORTED, AND TIED PER ACI 318 WITH SPECIFIED CONCRETE COVER.
 - BAR SPLICES AND HOOKS
SPLICES SHALL CONFORM TO THE BUILDING CODE AND BE CLASS B, UNLESS NOTED OTHERWISE. SPLICE LENGTH FOR BARS OF DIFFERENT SIZES SHALL BE BASED ON THE SMALLER BAR. HOOKS AND BENDS SHALL COMPLY WITH APPLICABLE CODE STANDARDS.
 - SLUMP AND AIR CONTENT
SLUMP SHALL BE 1" TO 4", MEASURED PER ASTM C143. PUMPED CONCRETE MAY ACCOUNT FOR SLUMP LOSS BUT SHALL REMAIN WITHIN LIMITS. AIR CONTENT SHALL BE 5-7% FOR 3/4" OR 1" AGGREGATE, AND 5.5-8% FOR 1/2", PER ASTM C231, C173, OR C138.
 - PLACING AND CONSOLIDATION
PLACE CONCRETE CONTINUOUSLY WITHIN JOINTS. DO NOT FREE-FALL MORE THAN 4 FEET. USE INTERNAL VIBRATION TO ENSURE FULL CONSOLIDATION. PROTECT CONCRETE FROM SEGREGATION DURING PLACEMENT.
 - CURING
CURE CONCRETE PER ASTM C309 OR WITH MOIST COVERINGS. MAINTAIN CURING FOR AT LEAST 7 DAYS. BEGIN CURING AS SOON AS SURFACE WATER HAS EVAPORATED. CONTINUE CURING IF FORMS ARE REMOVED EARLY.
 - WEATHER PROTECTION
COMPLY WITH ACI 305R AND 306R FOR HOT AND COLD WEATHER. DO NOT PLACE CONCRETE ON FROZEN SUBGRADE OR ABOVE 90°F WITHOUT PROPER MEASURES. PREVENT RAPID EVAPORATION TO REDUCE CRACKING RISK.
 - CHAMFERS
UNLESS NOTED OTHERWISE, PROVIDE 3/4" CHAMFERS AT EXPOSED CONCRETE CORNERS AND EDGES. RE-ENTRANT CORNERS SHALL HAVE FILLETS WHERE SHOWN.
 - FIELD TESTING
TESTING SHALL CONFORM TO:
SAMPLING & CURING: ASTM C172, C31
COMPRESSIVE STRENGTH: ASTM C39 (1 TEST AT 7 DAYS, 2 AT 28 DAYS PER SET)
SLUMP: ASTM C143
AIR CONTENT: ASTM C231, C173, OR C138
MINIMUM TEST FREQUENCY: 1 SET PER 50 CY PLACED OR PER DAY/TYPE. CONCRETE IS ACCEPTABLE IF: AVERAGE OF 3 CONSECUTIVE TESTS ≥ FC
NO TEST IS MORE THAN 500 PSI BELOW FC
 - FINISHES
UNLESS NOTED OTHERWISE, PROVIDE A FLOAT FINISH. SLABS SHALL MEET CLASS B FLATNESS (1/4" IN 10 FT).
- NON-SHRINK GROUT
GROUT FOR BASE PLATES, EQUIPMENT ANCHORAGE AND GENERAL PURPOSES SHALL BE APPROVED, NON-SHRINK CEMENTITIOUS GROUT CONTAINING NATURAL AGGREGATES DELIVERED TO THE JOB SITE IN FACTORY PREPACKAGED CONTAINERS REQUIRING ONLY THE ADDITION OF WATER, ASTM C1107 TYPE B OR C.

F. WOOD

- FRAMING LUMBER
FRAMING LUMBER SHALL BE KILN DRIED OR MC-15, AND GRADED AND MARKED IN CONFORMITY WITH WEST COAST LUMBER INSPECTION BUREAU STANDARD GRADING RULES FOR WEST COAST LUMBER NO. 16, LATEST EDITION. FURNISH TO THE FOLLOWING MINIMUM STANDARDS: UNLESS NOTED OTHERWISE.
- 2X JOISTS AND BUILT-UP MEMBERS
HEM-FIR NO. 2
- 3X AND 4X BEAMS AND POSTS
DOUGLAS FIR-LARCH NO. 2
- BOLTED STUDS, LEDGERS AND PLATES
DOUGLAS FIR-LARCH STANDARD GRADE
- TREATED WOOD
ALL WOOD PLATES, LEDGERS, AND BLOCKING IN DIRECT CONTACT WITH CONCRETE OR MASONRY SHALL BE PRESSURE-TREATED WITH AN AMERICAN WOOD PRESERVERS ASSOCIATION (AWPA) APPROVED PRESERVATIVE. ALTERNATIVELY PER IBC SECTION 2304.11, FOR SOME EXCEPTIONS, IMPERVIOUS MOISTURE BARRIERS MAY BE PROVIDED BETWEEN UNTREATED MEMBERS AND CONCRETE OR MASONRY.
- ALL METAL FASTENERS IN CONTACT WITH TREATED WOOD SHALL BE GALVANIZED PER ASTM F2329 OR STAINLESS STEEL. WHEN USING GALVANIZED FASTENERS, THE CONTRACTOR SHALL VERIFY THE GALVANIZATION PROCESS WITH THE CHEMICAL COMPOSITION OF THE WOOD TREATMENT.
- TIMBER CONNECTORS
TIMBER CONNECTORS CALLED OUT BY LETTERS AND NUMBERS SHALL BE BY SIMPSON STRONG-TIE COMPANY, INC., AS SPECIFIED IN THE LATEST EDITION OF THEIR CATALOG. EQUIVALENT DEVICES BY OTHER MANUFACTURERS MAY BE SUBSTITUTED, PROVIDED THEY HAVE CURRENT ICC-ES EVALUATION REPORTS DEMONSTRATING THAT THE PRODUCTS HAVE EQUAL OR GREATER LOAD CAPACITIES. PROVIDE NUMBER AND SIZE OF FASTENERS AS SPECIFIED BY MANUFACTURER. CONNECTORS SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S PUBLISHED SPECIFICATIONS. WHERE CONNECTOR STRAPS CONNECT TWO MEMBERS, PLACE ONE-HALF OF THE NAILS OR BOLTS IN EACH MEMBER. ALL BOLTS IN WOOD MEMBERS SHALL CONFORM TO ASTM A307. PROVIDE WASHERS UNDER THE HEADS AND NUTS OF ALL BOLTS AND LAG SCREWS BEARING ON WOOD. UNLESS NOTED OTHERWISE, ALL NAILS SHALL BE COMMON. ALL SHIMS SHALL BE SEASONED AND DRIED AND THE SAME GRADE (MINIMUM) AS MEMBERS CONNECTED. ALL SINGLE JOISTS, DOUBLE JOISTS, AND TRIPLE JOISTS SHALL BE CONNECTED TO FLUSH BEAMS WITH "U" SERIES JOIST HANGERS.
- NAILS
 - NAILS SHALL BE GALVANIZED COMMON WIRE NAILS.
 - MINIMUM NAILING PER 2021 IBC TABLE 2304.10.2.
 - PRE DRILLED HOLES SHALL BE 1/16" LESS THAN SPIKE DIAMETER. WHERE SPLITTING OF WOOD MAY OCCUR, HOLES SHALL BE 1/32" LESS THAN NAIL DIAMETER AND DIAMETER OF NAIL LESS THAN THE PENETRATION OF THE NAIL.

G. STEEL

- CODE AND SPECIFICATIONS:
STEEL CONSTRUCTION SHALL CONFORM TO THE SPECIFICATIONS AND STANDARDS AS CONTAINED IN THE 15TH EDITION OF THE AISC MANUAL OF STEEL CONSTRUCTION. SHOP DRAWINGS SHALL BE SUBMITTED AND REVIEWED BY THE ENGINEER BEFORE COMMENCING FABRICATION.
- THE CONTRACTOR IS RESPONSIBLE FOR ALL ERECTION AIDS THAT INCLUDE, BUT ARE NOT LIMITED TO, ERECTION ANGLES, LIFT HOLES, AND OTHER AID.
- STEEL FABRICATOR SHALL BE CERTIFIED BY THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION AND SHALL BE A CATEGORY 'B' CERTIFICATION OR DEMONSTRATE A MINIMUM OF FIVE YEARS EXPERIENCE ON SIMILAR PROJECTS. QUALIFICATIONS SHALL BE SUBMITTED TWO WEEKS PRIOR TO BID.
- STEEL ERECTION SHALL BE PERFORMED BY AN ERECTOR CERTIFIED BY THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION OR DEMONSTRATE A MINIMUM OF FIVE YEARS EXPERIENCE ON SIMILAR PROJECTS. QUALIFICATIONS SHALL BE SUBMITTED TWO WEEKS PRIOR TO BID.
- MATERIAL PROPERTIES:
ALL STEEL SHAPES: ASTM A36 (Fy = 36 KSI)
BOLTS: ASTM A325N
- WELDING:
ALL WELDS SHALL BE PERFORMED IN ACCORDANCE WITH THE PROVISIONS OF AWS D.1, 'STRUCTURAL WELDING CODE'. ALL WELDERS SHALL BE AWS/WABO (WASHINGTON ASSOCIATION OF BUILDING OFFICIALS) CERTIFIED. WELDERS SHALL BE PREQUALIFIED FOR ALL WELD POSITIONS AND TYPES PERFORMED. WELDS SHOWN ON PLAN ARE MINIMUM SIZES, BASED ON PLATE THICKNESS. FIELD WELDING SYMBOLS HAVE NOT NECESSARILY BEEN INDICATED ON THE DRAWINGS. WHERE SHOWN, PROPER FIELD WELDING PER AWS D.1 SHALL BE FOLLOWED. WHERE NO FIELD WELDING SYMBOLS ARE SHOWN, IT IS THE CONTRACTOR'S RESPONSIBILITY TO COORDINATE THE USE OF SHOP AND FIELD WELDS. GALVANIZATION SHALL BE REMOVED PRIOR TO APPLYING FIELD WELDS AND RE-APPLIED PER SPECIFICATIONS.
- ALL WELDS SHALL BE MADE USING LOW HYDROGEN ELECTRODES WITH MINIMUM TENSILE STRENGTH PER AWS D.1 (MINIMUM 70 KSI). LOW HYDROGEN SMAW ELECTRODES SHALL BE USED WITHIN 4 HOURS OF OPENING THEIR HERMETICALLY SEALED CONTAINERS, OR SHALL BE REBAKED PER AWS D.1, SECTION 4.5. ELECTRODES SHALL BE REBAKED NO MORE THAN ONE TIME, AND ELECTRODES THAT HAVE BEEN WET SHALL NOT BE USED.
- ALL WELDING SHALL BE PERFORMED IN STRICT ADHERENCE TO A WRITTEN WELDING PROCEDURE SPECIFICATION (WPS) PER AWS D.1 OR AWS D.1.6. ALL WELDING PARAMETERS SHALL BE WITHIN THE ELECTRODE MANUFACTURER'S RECOMMENDATIONS. WELDING PROCEDURES SHALL BE SUBMITTED TO THE OWNER'S TESTING AGENCY FOR REVIEW BEFORE STARTING FABRICATION OR ERECTION. COPIES OF THE WPS SHALL BE ON SITE AND AVAILABLE TO ALL WELDERS AND THE SPECIAL INSPECTOR.

H. SPECIAL INSPECTION

IN ADDITION TO THE INSPECTIONS REQUIRED BY SECTION 1701 OF THE IBC, SPECIAL INSPECTIONS SHALL BE PROVIDED DURING CONSTRUCTION OF THE FOLLOWING WORK PER IBC SECTION 1705:


- ANCHOR BOLTS: INSTALLED IN CONCRETE OR MASONRY PRIOR TO AND DURING THE PLACEMENT OF CONCRETE AROUND BOLTS SHALL BE INSPECTED PERIODICALLY.
- ALL CONCRETE: SHALL BE INSPECTED IN ACCORDANCE WITH REQUIREMENTS OF 2021 IBC PARAGRAPH 1705.3.
- PLACEMENT: OF ALL REINFORCING STEEL SHALL BE INSPECTED PERIODICALLY.
- MECHANICAL FASTENERS: INSTALLED IN GROUTED MASONRY SHALL BE INSPECTED PERIODICALLY.
- EPOXY ANCHORS:
INSTALLED IN GROUTED MASONRY SHALL BE INSPECTED CONTINUOUSLY.

I. STRUCTURAL OBSERVATIONS


THE ENGINEER OF RECORD SHALL PROVIDE VISUAL OBSERVATION OF THE STRUCTURAL SYSTEM, FOR GENERAL CONFORMANCE TO THE APPROVED PLANS AND SPECIFICATIONS, AT SIGNIFICANT CONSTRUCTION STAGES AND AT THE COMPLETION OF THE STRUCTURAL SYSTEM. STRUCTURAL OBSERVATION DOES NOT INCLUDE OR WAIVE THE RESPONSIBILITY FOR THE INSPECTIONS REQUIRED BY IBC SECTIONS 109, 1704 OR OTHER SECTIONS OF THE INTERNATIONAL BUILDING CODE. STRUCTURAL OBSERVATION REPORTS SHALL BE ISSUED TO THE OWNER, ARCHITECT, CONTRACTOR, AND BUILDING OFFICIAL AT THE SIGNIFICANT CONSTRUCTION STAGES.

Call 48 Hours
Before You Dig


1-800-424-5555
UNDERGROUND SERVICE



ISSUED FOR BID	08/2025	MDW	KED
No.	Revision	Date	By



N 1 ADMINISTRATION BUILDING ROOF PLAN



ISSUED FOR BID	08/2025	MDW	KED
Revision	Date	By	App'd



Seattle // Spokane // Baltimore
Copyright © FSI consulting engineers



BHC Consultants, LLC
1601 Fifth Avenue, Suite 500
Seattle, Washington 98101
206.505.3400 (fax)
www.bhconsultants.com

Designed: M Wildhood, P.E.	Scale: As Noted
Drawn: R. Rhodes	One Inch at Full Scale
Checked: N. Jacoby, P.E., S.E.	If Not One Inch Scale Accordingly





Kitsap County Public Works
18 57 KITSAP COUNTY
WASHINGTON

KITSAP COUNTY SEWER UTILITY (KCU) CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC SYSTEM REPLACEMENT
ADMINISTRATION BUILDING ROOF PLAN AND DETAIL



Drawing: S.1.01
Sheet: 16 of 47
File: P23-10865_S1.01
Date: September 2025



ISSUED FOR BID	08/2025	MDW	KED
Revision	Date	By	App'd



Seattle // Spokane // Baltimore
Copyright © fsi consulting engineers



bhc
CONSULTANTS
BHC Consultants, LLC
1601 Fifth Avenue, Suite 500
Seattle, Washington 98101
206.505.3400 (fax)
www.bhconsultants.com


Designed: M Wildhood, P.E.	Scale:
Drawn: R. Rhodes	As Noted
Checked: N. Jacoby, P.E., S.E.	One Inch at Full Scale If Not One Inch Scale Accordingly



Kitsap County Public Works
18 57 KITSAP COUNTY
614 Division Street, MS 26
Port Orchard, WA 98366

KITSAP COUNTY SEWER UTILITY (KCU) CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC SYSTEM REPLACEMENT
ADMINISTRATION BUILDING SKYLIGHT SUPPORT SECTIONS AND DETAILS

Call 48 Hours
Before You Dig
1-800-424-5555
UNDERGROUND SERVICE



Drawing: S2.01
Sheet: 17 of 47
File: P23-10865_S2.01
Date: September 2025

MECHANICAL COMPLIANCE SUMMARY

2021 WSEC Compliance Forms for Commercial Buildings including Group R1, R2, and Group R3 & R4 over 3 stories

Administered by: ©2021 NEEA, All rights reserved

Project & Applicant Information	Project Title	Kitsap County Sewer Utility (KCU) Central Kitsap Treatment Plant (CKTP) HVAC System Replacement - 2021 WSEC			For Building Department Use: Date: May 27, 2025
	Project Address	614 Division Street, MS 26 Port Orchard, WA 98366			
	Applicant Name	Brent Quigley			
	Applicant Phone	206-385-6144			
	Applicant Email	brentq@fsi-engineers.com			

Mechanical Compliance Summary Scope - Compliance verification provided in this report is limited to code minimum efficiency requirements for mechanical equipment types defined in Tables C403.3.2(1) through C403.3.2(16) of the 2021 WSEC-C. This includes efficiency multipliers for economizer exceptions. Performance criteria for additional energy efficiency and load management measures ARE NOT included in this report. Additional documentation is required to demonstrate compliance with all other provisions of the energy code, including better than code efficiency criteria for Section C406. For questions about this report, contact WSEC Commercial Technical Support at 360-539-5300 or via email at com.techsupport@waenergycodes.com.

General Occupancy	All Commercial	General Building Use Type(s)	Industrial		Building Cond. Floor Area	4,600
General Project Types	Alteration	New Building or Addition Mechanical Scope	Alteration Mechanical Scope		Multiple Zone Systems & Equipment	Project Cond. Floor Area 4,600 Floors Above Grade 1 Overall Compliance Path General Prescriptive
Mechanical Project Description	Demolition of existing air handler unit, ductwork, replacement with new air handler, variable air volume boxes, and energy-recovery ventilators.					

Mechanical Compliance Scope and Method	Project Type	Mechanical Scope	Economizer Exception(s) Applied?	DOAS Ventilation Provided?	Equipment Efficiency Compliance Verification
	Alteration	Multiple Zone Systems & Equipment	Yes	Yes	COMPLIES
Additional Energy Efficiency Measures (AEM)	No mechanical additional energy efficiency measures included in project		Load Management Measures (LDM)	No mechanical load management measures included in project	
Does building include occupancy classifications requiring DOAS?	No		Does project include DOAS equipment?	Yes	
Based on project scope do TSPr requirements apply?	No		Do all systems comply with Appendix D standard reference design or qualify for an exception to TSPr?	Yes	

Scope & Space Conditioning	ALTERATION - MULTIPLE ZONE SYSTEMS & EQUIPMENT	Compliance Verification	COMPLIES
----------------------------	--	-------------------------	----------

Multiple Zone Air Systems Category - Heat pump, split & single package

Air Systems Summary Information

System/Equip ID	Supply Airflow Control	Ventilation Standard	Ventilation CFM	Ventilation Air Source	Paired with DOAS	Ventilation energy recovery	Energy Recovery Efficiency (%)
CU-1, FCU-1	VAV with zone return or exhaust control	IMC Multiple Zones Ventilation	630	Separate DOAS	ERV-1, ERV-2	Yes per C403.5 Energy Recovery	75.9
CU-2, FCU-2	VAV with zone return or exhaust control	IMC Multiple Zones Ventilation	765	Separate DOAS	ERV-1, ERV-2	Yes per C403.5 Energy Recovery	75.9
CU-3	Constant volume	IMC Multiple Zones Ventilation	85	Separate DOAS	ERV-3	Provided but not required	74.7

Air Systems & Equipment - Cooling											
System/Equip ID	Cooling System/Equip Type	Specific Type	Cooling Capacity (Btu/h)	Econo Exception Multipliers (Full/PLV)	Required Cooling Efficiency (Code Min + Econo)	Required Part Load Efficiency (Code Min + Econo)	Proposed Cooling Efficiency	CE Units	Proposed Part Load Efficiency	PL Units	Efficiency Compliance Verification
CU-1, FCU-1	Heat pump, air cooled	Split system	36,100	1.0 1.0	14.3	0	23	SEER2		IEER	COMPLIES
CU-2, FCU-2	Heat pump, air cooled	Split system	36,100	1.0 1.0	14.3	0	23	SEER2		IEER	COMPLIES
CU-3	Heat pump, air cooled	Split system	18,000	1.0 1.0	14.3	0	15.2	SEER2		IEER	COMPLIES

Air Systems & Equipment - Heating											
System/Equip ID	Heating System/Equip Type	Specific Type	Heat Pump Heating Capacity (Btu/h)	Cooling Capacity (Btu/h) (Identical to Cooling Table)	Required Heat Pump Heating Efficiency	Required Low OSA Temp Efficiency	Proposed Heat Pump Heating Efficiency	HPH Units	Proposed Low OSA Temp Efficiency	LTH Units	Efficiency Compliance Verification
CU-1, FCU-1	Heat pump, air cooled, heating	Split system	36,960	36,100	7.5	0	9.6	HSPF2		COP	COMPLIES
CU-3	Heat pump, air cooled, heating	Split system	17,400	18,000	7.5	0	7.8	HSPF2		COP	COMPLIES
CU-2, FCU-2	Heat pump, air cooled, heating	Split system	36,960	36,100	7.5	0	9.6	HSPF2		COP	COMPLIES

System/Equip ID	Discrete Area(s) Served	Location In Project Documents - Plan/Detail #			System/Equip Compliance Path		
CU-1, FCU-1	Lab	M4.01, M5.01			General Prescriptive		
	Heating Section/Auxiliary Heating Type: Electric resistance (or None)				Economizer Compliance Method: Applying air-side economizer exception		
	Air-side economizer exception applied: Exp 1 - DOAS paired with cooling system (Note equip location limitations)						
	WSEC Equip Efficiency Reference Table - Cooling: Table C403.3.2(2) Unitary Air-Cooled Heat Pumps						
	WSEC Equip Efficiency Reference Table - Heating: Refer to Cooling Reference Table						
CU-2, FCU-2	Lab	M4.01, M5.01			General Prescriptive		
	Heating Section/Auxiliary Heating Type: Electric resistance (or None)				Economizer Compliance Method: Applying air-side economizer exception		
	Air-side economizer exception applied: Exp 1 - DOAS paired with cooling system (Note equip location limitations)						
	WSEC Equip Efficiency Reference Table - Cooling: Table C403.3.2(2) Unitary Air-Cooled Heat Pumps						
	WSEC Equip Efficiency Reference Table - Heating: Refer to Cooling Reference Table						
CU-3	Back of House	M4.01, M5.01			General Prescriptive		
	Heating Section/Auxiliary Heating Type: Electric resistance (or None)				Economizer Compliance Method: Applying air-side economizer exception		
	Air-side economizer exception applied: Exp 1 - DOAS paired with cooling system (Note equip location limitations)						
	WSEC Equip Efficiency Reference Table - Cooling: Table C403.3.2(2) Unitary Air-Cooled Heat Pumps						
	WSEC Equip Efficiency Reference Table - Heating: Refer to Cooling Reference Table						

No.	Revision	Date	By	App'd	Designed: MSS	Scale: N/A
					Drawn: WHB	One Inch at Full Scale If Not One Inch Scale Accordingly
					Checked:	




Call 48 Hours
Before You Dig
1-800-424-5555
UNDERGROUND SERVICE

GENERAL NOTES

- DEMOLISH SYSTEMS IN WEST AND EAST LABS IN COMPLIANCE WITH COUNTY-APPROVED LAB CONSTRUCTION PHASING PLAN.

DEMOLITION NOTES

- REMOVE EXISTING HEAT RECOVERY UNIT, DUCTWORK, AND PIPING CONNECTIONS. MAINTAIN OUTSIDE AIR AND EXHAUST LOUVERS.
- REMOVE EXISTING HEATING HOT WATER HWS/R PIPING, VALVES AND SUPPORTS TO HEAT RECOVERY UNIT.
- REMOVE EXISTING HEATING HOT WATER HWS/R PIPING AND SUPPORTS WITHIN LAB 102 ROUTING TO LAB 101.
- MANTAIN AND PROTECT EXISTING FUME HOOD. TAKE AIRFLOW READINGS OF EXHAUST FANS PRIOR TO DEMOLITION WORK FOR RECORD.
- MANTAIN AND PROTECT EXISTING DUCTWORK FOR REUSE AND FUTURE TIE IN.
- REMOVE EXISTING DUCTWORK, DIFFUSERS, GRILLES, SUPPORTS, AND APPURTENANCES.
- REMOVE EXISTING CABINET HEATER, HEATING HOT WATER VALVES, AND HEATING HOT WATER PIPING. CAP PIPING AT FLOOR AND LEAVE PIPING UNDER SLAB ABANDONED IN PLACE.
- MANTAIN AND PROTECT EXISTING EXHAUST FAN AND DUCTWORK FOR LAB HOOD EXHAUST.
- REMOVE EXISTING EXHAUST FAN AND DUCTWORK AND PATCH ROOF PENETRATION.
- REMOVE EXISTING THROUGH WALL AIR CONDITIONING UNIT. OPENING TO BE ENCLOSED BY NEW WINDOW PER ARCHITECTURAL DRAWINGS.
- REMOVE EXISTING SPLIT SYSTEM OUTDOOR AND INDOOR UNITS AND ASSOCIATED PIPING AND RETURN TO OWNER. PATCH WALL PENETRATIONS.
- REMOVE EXISTING CONDENSING UNIT, ASSOCIATED PIPING, AND CONCRETE PAD.
- MANTAIN AND PROTECT EXISTING SPLIT SYSTEM OUTDOOR AND INDOOR UNITS.
- MANTAIN AND PROTECT DOMESTIC HOT WATER PIPING AND WATER HEATER IN MECHANICAL ROOM.
- REMOVE EXISTING HOT WATER HWS/R PIPING AND SUPPORTS THROUGH TRANSFER STRUCTURE AND IN MECHANICAL ROOM.
- REMOVE HEATING HOT WATER VALVES, SUPPORTS, AND COMPONENTS AND CAP AT FLOOR LEVEL.
- MANTAIN AND PROTECT EXISTING EXHAUST FAN AND REWORK DUCTWORK AS NEEDED, FOR MUFFLE FURNACE.



1 LAB-ADMIN BUILDING - HVAC DEMOLITION FLOOR PLAN

SCALE: 1/4" = 1'-0"

4 3 2 1 0 4 8 12
SCALE: 1/4" = 1'-0" FEET

Revision	Date	By	App'd



Seattle // Spokane // Baltimore
Copyright © fsi consulting engineers

Designed: MSS

Drawn: WHB

Checked:

Scale:

1/4" = 1'-0"

One Inch at Full Scale

If Not One Inch

Scale Accordingly



Kitsap County Public Works
18 57
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES

**LAB-ADMIN BUILDING
HVAC DEMOLITION FLOOR PLAN**

Drawing: **MD1.01**


Sheet: **20** of **47**

File: **COMPLETE**

Date: **September 2025**

Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE




GENERAL NOTES

1. INSTALL SYSTEMS IN WEST AND EAST LABS IN COMPLIANCE WITH COUNTY-APPROVED LAB CONSTRUCTION PHASING PLAN.
2. PROVIDE FLEX DUCT TO ALL INLET AND OUTLET CONNECTIONS.

CONSTRUCTION NOTES

- 1 PROVIDE AND INSTALL FAN COIL UNIT TO BE MOUNTED ABOVE CEILING. PROVIDE CONDENSATE DRAINAGE PIPING AND ROUTE TO NEAREST SINK TAIL PIECE.
- 2 PROVIDE AND INSTALL EXPOSED DUCTWORK AND SUPPORTS TIGHT TO ROOF STRUCTURE. MAINTAIN MANUFACTURER'S CLEARANCE REQUIREMENTS OF WALL MOUNTED SPLIT UNITS.
- 3 ROUTE DUCTWORK IN EXISTING DUCT TRANSFER STRUCTURES.
- 4 PROVIDE AND MOUNT WALL THERMOSTAT.
- 5 ROUTE DUCTWORK THROUGH EXISTING INTERIOR WALL. REFER TO ARCHITECTURAL DETAILS ON A1.12 FOR WALL PENETRATION REQUIREMENTS.
- 6 PROVIDE AND INSTALL EXTERIOR CONDENSING UNIT ON PLASTIC CONDENSING UNIT PAD. PROVIDE REFRIGERANT PIPING AND ROUTE THROUGH NEW WALL PENETRATION TO INTERIOR UNIT. REFER TO ARCHITECTURAL DETAILS ON A1.12 FOR WALL PENETRATION REQUIREMENTS. COORDINATE LOCATION WITH OWNER PRIOR TO INSTALLATION.
- 7 PROVIDE REFRIGERANT PIPING AND CONNECT TO FAN COIL UNIT. ROUTE PIPING TO EXTERIOR CONDENSING UNIT (CU-4).
- 8 PROVIDE REFRIGERANT PIPING AND CONNECT TO FAN COIL UNIT. ROUTE PIPING TO EXTERIOR CONDENSING UNIT (CU-5).
- 9 PROVIDE AND INSTALL WALL MOUNTED SPLIT UNIT AND PROVIDE REFRIGERANT CONDENSATE PIPING. ROUTE REFRIGERANT PIPING TO EXTERIOR CONDENSING UNIT (CU-3). DRAIN CONDENSATE TO EXTERIOR. PROVIDE NEW WALL PENETRATIONS AND REFER TO ARCHITECTURAL DETAILS ON A1.12 FOR WALL PENETRATION REQUIREMENTS.
- 10 REPLACE EXISTING REFRIGERANT PIPING CURRENTLY SERVING CU-2 AND SS-2.



1 LAB-ADMIN BUILDING - HVAC FLOOR PLAN

SCALE: 1/4"=1'-0"

Revision	Date	By	App'd



Seattle // Spokane // Baltimore
Copyright © FSi consulting engineers

Designed: MSS

Scale:

1/4" = 1'-0"

Drawn: WHB

One Inch at Full Scale

If Not One Inch

Scale Accordingly

Checked:




Kitsap County Public Works
18 57
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES

**LAB-ADMIN BUILDING
HVAC FLOOR PLAN**

Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE



Drawing: M1.01

Sheet: 21 of 47

File: COMPLETE


Date: September 2025

4 3 2 1 0 4 8 12
SCALE: 1/4" = 1'-0"
FEET

09/25/2025
SIGNED

CONSTRUCTION NOTES


- 1 ▶ PROVIDE AND INSTALL ENERGY RECOVERY VENTILATOR UNIT ON 4" HOUSEKEEPING PAD.
- 2 ▶ PROVIDE AND INSTALL EXTERIOR CONDENSING UNIT ON PLASTIC CONDENSING UNIT PAD.
- 3 ▶ PROVIDE AND MOUNT ENERGY RECOVERY VENTILATOR UNIT ON WALL.
- 4 ▶ PROVIDE DUCT PLENUM BOX AND CONNECT TO EXISTING LOUVER. PROVIDE FLANGED CONNECTIONS FROM DUCTWORK TO PLENUM BOX.
- 5 ▶ ROUTE REFRIGERANT PIPING THROUGH NEW WALL PENETRATION. REFER TO ARCHITECTURAL DETAILS ON A1.12 FOR WALL PENETRATION REQUIREMENTS.
- 6 ▶ MAINTAIN A MIN. 36" CLEAR FROM FRONT OF NEW ELECTRICAL PANEL.
- 7 ▶ ROUTE DUCTWORK THROUGH EXISTING WALL PENETRATION. CONTRACTOR SHALL PROVIDE DUCT TRANSITIONS FOR FIRE DAMPERS AND DUCTWORK THROUGH EXISTING WALL PENETRATIONS.
- 8 ▶ ROUTE DUCTWORK THROUGH EXISTING INTERIOR WALL. REFER TO ARCHITECTURAL DETAILS ON A1.12 FOR WALL PENETRATION REQUIREMENTS.
- 9 ▶ PROVIDE IN-LINE DIRECT EXPANSION COIL AND ROUTE CONDENSATE TO NEAREST FLOOR DRAIN.



ENLARGED PLAN - MECHANICAL ROOM

SCALE: 1/2"=1'-0"

M1.01 M4.01



SECTION VIEW - MECHANICAL ROOM

SCALE: 1/2"=1'-0"

M4.01 M4.01

No.	Revision	Date	By	App'd



Seattle // Spokane // Baltimore
Copyright © FSi consulting engineers

Designed: MSS	Scale: 1/4" = 1'-0"
Drawn: WHB	One Inch at Full Scale If Not One Inch Scale Accordingly
Checked:	



KITSAP COUNTY
18 57
KITSAP COUNTY
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES

LAB-ADMIN BUILDING
HVAC ENLARGED PLANS




Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE

Drawing: M4.01
Sheet: 22 of 47
File: COMPLETE
Date: September 2025


CONSTRUCTION NOTES

- 1 ▶ PROVIDE AND INSTALL ENERGY RECOVERY VENTILATOR UNIT ON 4" HOUSEKEEPING PAD.
- 2 ▶ PROVIDE AND MOUNT ENERGY RECOVERY VENTILATOR UNIT ON WALL. CONTRACTOR TO PROVIDE UNISTRUT AND ANGLE BRACKET DESIGN TO SUPPORT UNIT FROM BOTTOM TO WALL FOR ENGINEER REVIEW. REFER TO STRUCTURAL NOTES ON S1.01 FOR ADDITIONAL LOADING REQUIREMENTS.
- 3 ▶ PROVIDE AND INSTALL 24"X22" PLENUM BOX OVER EXISTING LOUVER. PROVIDE FLANGED CONNECTIONS FROM DUCTWORK TO PLENUM BOX.
- 4 ▶ MAINTAIN A MIN. 36" CLEAR FROM FRONT OF NEW ELECTRICAL PANEL.



CONSTRUCTION NOTES

- 1 PROVIDE AND INSTALL ENERGY RECOVERY VENTILATOR UNIT ON WALL.
- 2 PROVIDE AND INSTALL 68"X40" PLENUM BOX OVER EXISTING LOUVER. PROVIDE FLANGED CONNECTIONS FROM DUCTWORK TO PLENUM BOX.
- 3 MAINTAIN A MIN. 36" CLEAR FROM FRONT OF NEW ELECTRICAL PANEL.



SECTION VIEW - MECHANICAL ROOM

SCALE: 1/2"=1'-0"

Call 48 Hours Before You Dig

1-800-424-5555
UNDERGROUND SERVICE

UNDERGROUND SERVICE



 **ENGINEERS**
Seattle // Spokane // Baltimore
Copyright © FSi consulting engineers

Designed: MSS

Drawn: WHB

Checked:

Scale:
1/4
One Inch
If Not
Scale A




Kitsap County Public Works
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES

LAB-ADMIN BUILDING HVAC SECTIONS

DRAWING
Drawing: **M4.03**
Sheet: **24** of **47**
File: **COMPLETE**
Date: **September 2025**


1 PROVIDE AND INSTALL DUCTWORK WITHIN EXISTING DUCT TRANSFER STRUCTURE.



SECTION VIEW -

SCALE: 1/2"=1'-0"

M1.01 M4.04



**Call 48 Hours
Before You Dig**

**Call 48 Hours
Before You Dig**

A circular seal for Kevin M. Chady, Professional Engineer, State of Washington. The outer ring contains the text "KEVIN M. CHADY" at the top and "PROFESSIONAL ENGINEER" at the bottom. The inner circle features a profile of a person's head facing left, with "STATE OF WASHINGTON" written above it and "NO. 5329" below it. The entire seal is rendered in black and white.

09.2025
SIGNED

Drawing: M4.04

Drawing: M4.04

Sheet: 25 of 47

File: **COMPLETE**

File: COMPLETE

Date: September 2025

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES

LAB-ADMIN BUILDING

HVAC SECTIONS



FSI ENGINEERS
Seattle // Spokane // Baltimore
Copyright © FSI consulting engineers

Designed: MSS	Scale: 1/4"
Drawn: WHB	One Inch If Not Scale A
Checked:	

VRV SPLIT SYSTEM UNIT SCHEDULE																												
CALLOUT		LOCATION	AREA SERVED	UNIT CONFIGURATION	RATED UNIT EFFICIENCY [1]	INDOOR FAN			COOLING			HEATING			REFER TYPE	OPERATING WEIGHT (LBS)	ELECTRICAL [7][8]					BASIS OF DESIGN		NOTES				
						CFM	ESP (IN WC) [2] [3]	NOMINAL CAPACITY (TONS) [5]	TOTAL COOLING (BTUH)	SENSIBLE COOLING (BTUH)	HEATING CAPACITY (BTUH) [5]	MIN EFFICIENCY (HSPF2)																
												V	HZ	Ø			MOPC	MCA	MANUFACTURER	MODEL								
FCU	1	WEST LAB	WEST LAB	DUCTED	—	1130	0.5	3	36000	23250	36960	—	R32	105	208	60	1	15	3	DAIKIN	FXMA36AAVJU							
FCU	2	EAST LAB	EAST LAB	DUCTED	—	1130	0.5	3	36000	23250	36960	—	R32	105	208	60	1	15	3	DAIKIN	FXMA36AAVJU							
DX	1	MECH ROOM	BACK OF HOUSE	IN-LINE DUCTED	—	—	—	1.5	18000	—	17400	—	R32	55	—	—	—	—	—	—	DAIKIN	CHPTA1822B3						
CU	1	OUTSIDE	ERV-3	—	12.5/15.2	—	—	1.5	18000	—	17400	7.8	R32	160	208	60	1	15	11.4	DAIKIN	DH4SEA1810							
CU	3	OUTSIDE	SS-3, SS-4, SS-5	—	12/21	—	—	2	23000	—	24000	10	R32	140	208	60	1	25	19.9	DAIKIN	3MXM24AVJU9							
CU	4	OUTSIDE	FCU-1	—	12/23	—	—	3	36100	—	36960	9.6	R32	175	208	60	1	20	19.8	DAIKIN	RXTQ36TBVJUB							
CU	5	OUTSIDE	FCU-2	—	12/23	—	—	3	36100	—	36960	9.6	R32	175	208	60	1	20	19.8	DAIKIN	RXTQ36TBVJUB							
SS	3	GEN OFFICE	GENERAL OFFICE	WALL MOUNTED	—	300	—	1	12000	—	12000	—	R32	19	208	60	1	—	—	DAIKIN	FTXV12AVJU9							
SS	4	WORK STATION	WORK STATION	WALL MOUNTED	—	300	—	0.5	7000	—	7000	—	R32	19	208	60	1	—	—	DAIKIN	CTXV07AVJU9							
SS	5	OFFICE	OFFICE	WALL MOUNTED	—	300	—	0.5	7000	—	7000	—	R32	19	208	60	1	—	—	DAIKIN	CTXV07AVJU9							

SCHEDULE NOTES:

[1] TEST PROCEDURE: AHRI 210/240 OR AHRI 340/360

[2] STATIC PRESSURE EXTERNAL TO UNIT

[3] DOES NOT INCLUDE ALLOWANCE FOR FILTER LOADING

[5] NOMINAL TONNAGE INCLUDED FOR REFERENCE ONLY – DO NOT USE FOR FINAL SIZING OF EQUIPMENT

[6] MAXIMUM ALLOWABLE MOTOR BRAKEHORSE POWER AT MAX FLOW AND ESP PER FAN MOTOR

[7] SINGLE POINT CONNECTION. UNIT TO BE PROVIDED WITH DISCONNECT SWITCH

[8] POWER CONNECTION TO BE MADE TO CONDENSING UNIT WITH CONDUIT AND POWER CONNECTED TO INDOOR UNIT FROM OUTDOOR UNIT

ENERGY RECOVERY VENTILATOR SCHEDULE																																					
CALLOUT		LOCATION	SERVICE	SUPPLY FAN							RETURN FAN							FILTER		DX HEATING		NOTES	ELECTRICAL														
				FAN TYPE	DRIVE TYPE	CFM [1]	E.S.P. (IN WC) [2]	QTY	MOTOR		FAN TYPE	DRIVE TYPE	CFM [1]	E.S.P. (IN WC) [2]	QTY	MOTOR		TYPE	MAX VEL	TOTAL HEATING (MBH)	MAX SOUND LEVEL (DBA)	OPERATING WEIGHT (LBS)	UNIT			PREHEATER		BACKUP HEATER									
									HP	BHP								HP	BHP				V	Hz	PH	MCA	V	KW	MCA	V	KW	MCA					
ERV	1	OUTSIDE WEST LAB	WEST LAB	PLENUM	DIRECT	630	1.0	1	2311	1	1/2	PLENUM	DIRECT	630	1.0	1	2291	1	1/2	MERV 13	500	—	70	610	208	60	1	9.06	208	5	30.06	208	2	12.03			
ERV	2	OUTSIDE EAST LAB	EAST LAB	PLENUM	DIRECT	760	1.0	1	2822	1	1/2	PLENUM	DIRECT	760	1.0	1	2344	1	1/2	MERV 13	500	—	70	610	208	60	1	9.06	208	5	30.06	208	2	12.03			
ERV	3	LAB/ADMIN MECH ROOM	BACK OF HOUSE	PLENUM	DIRECT	735	1.0	1	2348	1	1/2	PLENUM	DIRECT	735	1.0	1	2426	1	1/2	MERV 8	500	17.4	70	610	208	60	1	9.06	—	—	—	208	5	30.06	—	—	—
ERV	4	LAB/ADMIN MECH ROOM	OFFICE	PLENUM	DIRECT	85	0.5	1	4165	1/8	0.07	PLENUM	DIRECT	85	0.5	1	3861	1/8	0.07	MERV 8	500	—	70	35	120	60	1	15	120	1	8.33	—	—	—			

ENERGY RECOVERY VENTILATOR SCHEDULE - CONTINUED																									
CALLOUT		ENERGY RECOVERY																							

<p>SEQUENCE OF OPERATION – VRF/FCU</p> <p>GENERAL SYSTEM DESCRIPTION AND REQUIREMENTS:</p> <p>THE FAN COIL UNITS (FCU) ARE EQUIPPED WITH VARIABLE REFRIGERANT FLOW OR VARIABLE REFRIGERANT VOLUME (VRF/VRV). THE FCUs SHALL BE FULLY CONTROLLED BY THE MANUFACTURER'S ELECTRONIC CONTROLLERS AND CONTROL SYSTEM.</p> <p>PROVIDE GRAPHICAL DISPLAY AND INTERFACE (INTELLIGENT TOUCH MODULE) TO THE SYSTEM DESCRIBED IN THIS DOCUMENT AND SHOWN ON THE DESIGN DRAWINGS. INCLUDE AND PROVIDE ACCESS TO ALL POINTS AVAILABLE TO THE VRF SYSTEM INTERFACE MODULE. ALL SETPOINTS, TIME SCHEDULE SETTINGS AND OTHER VALUES SHALL BE OPERATOR ADJUSTABLE UNLESS INDICATED OTHERWISE.</p> <p>PROVIDE ROOM THERMOSTATS/SENSORS WITH THE ABILITY TO TEMPORARILY PLACE THE SYSTEM IN OCCUPIED MODE.</p> <p>PROVIDE ROOM THERMOSTATS/SENSORS WITH THE ABILITY TO ADJUST SETPOINTS $+\text{-} 3^{\circ}\text{ F}$.</p> <p>INITIAL DEFAULT ROOM TEMPERATURE SETPOINTS SHALL BE 68 DEGREES FOR HEATING AND COOLING.</p> <p>UNIT OPERATION:</p> <p>THE UNIT SHALL BE FULLY CONTROLLED BY THE MANUFACTURER'S CONTROL SYSTEM.</p> <p>THE VRF SYSTEM SHALL INDEX THE SYSTEM TO OCCUPIED MODE AT 7:00 AM TO 6:00 PM. WHEN NOT IN OCCUPIED MODE THE VRF SYSTEM SHALL INDEX THE SYSTEM TO UNOCCUPIED MODE.</p> <p>THE OCCUPANTS SHALL HAVE THE ABILITY TO INDEX THE SYSTEM TO OCCUPIED MODE FOR ADJUSTABLE TIME PERIOD WHEN THE SYSTEM IS INDEXED TO UNOCCUPIED MODE.</p> <p>OUTSIDE AIR/VENTILATION CONTROL</p> <p>THE ERV SHALL RECEIVE AN ENABLE COMMAND FROM THE VRF SYSTEM</p>	<p>CONTROLLER WHEN THE VRF SYSTEM IS IN OCCUPIED MODE. THE ERV SHALL MAINTAIN OCCUPIED/ENABLE STATUS THROUGHOUT SCHEDULED OR UNSCHEDULED OCCUPANCY.</p> <p>TEMPERATURE CONTROL</p> <p>THE VRF SYSTEM SHALL MONITOR THE INDIVIDUAL SPACE TEMPERATURES SERVED BY THE FCU.</p> <p>THE VRV/VRF CONTROLLER SHALL MODULATE THE SYSTEM TO MAINTAIN SPACE TEMPERATURE SETPOINT.</p> <p>WHEN THE ZONE SPACE TEMPERATURE SETPOINT IS ACHIEVED THE SYSTEM CONTROLLER SHALL INDEX THE FCU ASSOCIATED WITH THE ZONE TO STANDBY MODE. THE SYSTEM CONTROLLER SHALL ENABLE FCU OPERATION WHEN THE ZONE SPACE TEMPERATURE IS 1° F ABOVE OR BELOW SETPOINT.</p> <p>NIGHT SETBACK:</p> <p>WHEN UNIT IS IN UNOCCUPIED MODE AND THE SPACE TEMPERATURE REACHES 65° F, THE VRF SYSTEM SHALL ENABLE FCUs IN THE CORRESPONDING ZONE. WHEN THE ZONE/SPACE TEMPERATURE REACHES 70° F THE VRF SYSTEM SHALL TOGGLE BACK TO UNOCCUPIED MODE.</p> <p>NIGHT SETUP:</p> <p>WHEN UNIT IS IN UNOCCUPIED MODE AND THE SPACE TEMPERATURE REACHES 85° F, THE VRF SYSTEM SHALL ENABLE FCUs IN THE CORRESPONDING ZONE. WHEN THE ZONE/SPACE TEMPERATURE REACHES 80° F THE VRF SYSTEM SHALL TOGGLE BACK TO UNOCCUPIED MODE.</p> <p>MORNING WARM-UP/COOL-DOWN OPTIMIZATION</p> <p>THE CONTROL SYSTEM SHALL "LEARN" THE THERMAL CHARACTERISTICS OF THE BUILDING AND AIR DISTRIBUTION SYSTEMS TO PROVIDE OPTIMUM START TIMES FOLLOWING NIGHT SETBACK AND NIGHT SETUP. THE OPTIMUM START TIMES SHALL BE BASED ON LOGGED WARM-UP TIMES, COOL-DOWN TIMES, OUTSIDE AIR TEMPERATURES AND TIME OF DAY. THE CONTROL SYSTEM SHALL REFINE THE OPTIMUM START TO BE THE LATEST TIME TO HAVE THE SPACES UP TO OCCUPIED TEMPERATURE BY THE BEGINNING OF THE OCCUPIED PERIOD.</p> <p>WHEN THE SYSTEM IS IN MORNING WARM-UP/COOL-DOWN MODE, THE CONTROL SYSTEM SHALL ENABLE THE ASSOCIATED INTERLOCKED EQUIPMENT.</p>	<p>OUTSIDE VENTILATION AIR SHALL NOT ENTER THE SYSTEM DURING MORNING WARM-UP AND MORNING COOL-DOWN. THE ERV/DOAS UNIT, SHALL NOT RUN DURING MORNING WARM-UP AND MORNING COOL-DOWN. OUTSIDE AIR DAMPERS SHALL REMAIN CLOSED AND OUTSIDE AIR FANS SHALL NOT RUN DURING MORNING WARM-UP AND MORNING COOL-DOWN.</p> <p>SAFETIES AND ALARMS:</p> <p>ANNUNCIATE ALARMS AT THE VRF SYSTEM'S INTELLIGENT TOUCH MODULE (VRF SYSTEM GRAPHICAL INTERFACE) WHEN ANY OF THE FOLLOWING EVENTS OCCUR.</p> <p>VFV/VRV</p> <p>ALL SYSTEM AND DIAGNOSTIC ALARMS FROM VRV/VRF SYSTEM.</p> <p>FAN FAILURE</p> <p>ALARM WHEN CONTROLLER SENDS START OR STOP SIGNAL TO FAN AND THERE IS NO PROOF OF STATUS ALIGNMENT FOR ONE (1) MINUTE.</p>
---	--	--

SEQUENCE OF OPERATIONS - ERV

GENERAL SYSTEM DESCRIPTION AND REQUIREMENTS:

THE ENERGY RECOVERY VENTILATORS (ERV) ARE EQUIPPED WITH ECM SUPPLY FAN AND ECM EXHAUST FAN. ERV-1 AND ERV-2 ARE EQUIPPED WITH SCR ELECTRIC PREHEAT AND SCR HEATING COILS, ERV-3 IS EQUIPPED WITH SCR HEATING COIL AND DIRECT EXPANSION COIL (DX-1), AND ERV-4 IS EQUIPPED WITH SCR PREHEAT COIL.

THE ERVS SHALL BE CONTROLLED BY THE MANUFACTURER PROVIDED ELECTRONIC CONTROLLER.

PROVIDE GRAPHICAL DISPLAY AND INTERFACE (INTELLIGENT TOUCH MODULE) TO THE SYSTEM DESCRIBED IN THIS DOCUMENT AND SHOWN ON THE DESIGN DRAWINGS. INCLUDE AND PROVIDE ACCESS TO ALL POINTS AVAILABLE TO THE ERV SYSTEM INTERFACE MODULE. ALL SETPOINTS, TIME SCHEDULE SETTINGS AND OTHER VALUES SHALL BE OPERATOR ADJUSTABLE UNLESS INDICATED OTHERWISE.

UNIT OPERATION:

THE UNIT SHALL BE FULLY CONTROLLED BY THE MANUFACTURER'S CONTROL SYSTEM.

THE ERV SHALL RECEIVE AN ENABLE SIGNAL FROM THE VRF/FCU SYSTEM WHEN THE SYSTEM IS IN OCCUPIED MODE.

ECM FAN MOTOR CONTROL:

THE ECM FAN SPEED FOR THE SUPPLY FAN AND EXHAUST FAN SHALL BE SET TO MAINTAIN THE AIRFLOW SPECIFIED ON THE EQUIPMENT SCHEDULE. THE AIR BALANCER SHALL DETERMINE THE FAN SPEED SETTINGS.

ERV SUPPLY TEMPERATURE SETPOINT RESET SCHEDULE:

OAT 65° F - SAT 72° F
OAT 75° F - SAT 70° F

PREHEAT: WHEN THE SUPPLY AIR TEMPERATURE IS 5°F BELOW THE SUPPLY AIR TEMPERATURE SETPOINT ENABLE THE ELECTRIC PREHEAT AND MODULATE THE SCR ELECTRIC HEATING COIL TO MAINTAIN THE SUPPLY AIR TEMPERATURE SETPOINT. THE SYSTEM CONTROLLER SHALL DISENGAGE THE ELECTRIC HEATING COIL WHEN THE SUPPLY AIR TEMPERATURE IS 2° F ABOVE SETPOINT.

FUME HOOD MAKEUP AIR (ERV-1 AND ERV-2 ONLY):

UPON A SIGNAL THAT WEST LAB FUME HOOD EXHAUST FAN (EF-1) IS ENABLED, ERV-1 EXHAUST FAN SHALL CEASE OPERATION AND SUPPLY FAN SHALL CONTINUE NORMAL OPERATION. ERV-1 EXHAUST FAN SHALL ENABLE ONCE EF-1 HAS SIGNALED BEING DISABLED.

UPON A SIGNAL THAT EAS

SAFETIES AND ALARMS

ANNUNCIATE ALARMS AT THE VRF SYSTEM'S INTELLIGENT TOUCH MODULE (VRF SYSTEM GRAPHICAL INTERFACE) WHEN ANY OF THE FOLLOWING EVENTS OCCUR.

AIR FILTERS

THE ERV CONTROLLER SHALL MONITOR THE DIFFERENTIAL PRESSURE SWITCH ACROSS SPECIFIED FILTERS AND SHALL PROVIDE AN ALARM WHEN THE PRESSURE DROP EXCEEDS THE SETPOINT.

ALL SYSTEM AND DIAGNOSTIC ALARMS FROM THE ERV SYSTEM.

FAN FAILURE


ALARM WHEN CONTROLLER SENDS START OR STOP SIGNAL TO FAN AND THERE IS NO PROOF OF STATUS ALIGNMENT FOR ONE (1) MINUTE.


**Call 48 Hours
Before You Dig**



1-800-424-5555

UNDERGROUND SERVICE





1 PROCESS BUILDING - HVAC FLOOR PLAN



Seattle // Spokane // Baltimore
Copyright © FSi consulting engineers

N

1

PROCESS BUILDING - HVAC FLOOR PLAN

SCALE: 1/4" = 1'-0"

Designed: MSS

Drawn: WHB

Checked:

Scale:

1/4" = 1'-0"

One Inch at Full Scale

If Not One Inch
Scale Accordingly



Kitsap County Public Works
18 57 614 Division Street, MS 26
Port Orchard, WA 98366


4 3 2 1 0 4 8 12
SCALE: 1/4" = 1'-0"
FEET

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES

**PROCESS BUILDING
HVAC FLOOR PLAN**

Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE



KEVIN M. CHADWICK
REGISTRATION NO. 329
08/2025
SIGNED
Drawing: M7.01
Sheet: 28 of 47
File: COMPLETE
Date: September 2025

No.	Revision	Date	By	App'd


CONSTRUCTION NOTES

- 1 PROVIDE AND INSTALL 1-1/2" MOTORIZED 2-WAY CONTROL VALVE ON EXISTING HEATING HOT WATER RETURN PIPING TO HEATING COIL. INSTALL CONTROL VALVE DOWNSTREAM OF EXISTING ISOLATION VALVE.
- 2 REMOVE EXISTING OUTSIDE AIR DAMPER AND DAMPER ACTUATOR. PROVIDE AND INSTALL NEW OUTSIDE AIR DAMPER AND DAMPER ACTUATOR. REPLACE SCREENING ON LOUVERS.
- 3 REMOVE EXISTING DAMPER ACTUATOR FOR BYPASS AIR DAMPER. PROVIDE AND INSTALL ACTUATOR FOR EXISTING MOTORIZED BYPASS AIR DAMPER.

CONSTRUCTION NOTES

1 EXISTING UNIT TO BE REMOVED AND REPLACED WITH ROOFTOP AIR CONDITIONING UNIT (ACU) OF EQUIVALENT FUNCTIONALITY. EXISTING MANUFACTURER, MODEL, AND SERIAL NUMBER ARE PROVIDED FOR REFERENCE: TRANE 4TCY4024A1000AA / SN: 10104LGY9H; ALL EXISTING FEATURES, INCLUDING BUT NOT LIMITED TO HEATER SIZE, PRESENCE OF CRANKCASE HEATER, PRESENCE OF ECONOMIZER, AND CURB COMPATIBILITY, SHALL BE MET BY THE REPLACEMENT UNIT. ACU UNIT COILS AND CONDENSER SHALL HAVE FACTORY-APPLIED HERESITE COATING; ALL EXTERNAL COMPONENTS SHALL ALSO HAVE APPROPRIATE CORROSION-RESISTANT COATINGS.

2 REPLACE THE EXISTING ROOFTOP ACU INCLUDING MINOR MODIFICATIONS (IF NEEDED) TO EXISTING CURB AND/OR ROOF STRUCTURE; CONNECT/DISCONNECT POWER; DELIVER, PLACE AND SECURE ACU ON ROOF; REMOVE OLD UNIT AND PROPERLY DISPOSE; CONDUCT START UP AND COMMISSIONING.



N 1 HEADWORK BUILDING - HVAC ROOF PLAN

SCALE: 1/2" = 1'-0"

Designed: MSS

Scale:

1/2" = 1'-0"

Drawn: WHB

One Inch at Full Scale

If Not One Inch

Scale Accordingly

Checked:

2 1 0 2 4 6
SCALE: 1/2" = 1'-0" FEET



Kitsap County Public Works
18 57 614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES

**HEADWORK BUILDING
HVAC ROOF PLAN**

Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE



KEVIN M. CHADWICK
REGISTERED ENGINEER
08/2025
SIGNED

M8.01

Sheet: 29 of 47

File: COMPLETE

Date: September 2025


No.	Revision	Date	By	App'd

fsi
ENGINEERS
Seattle // Spokane // Baltimore
Copyright © FSi consulting engineers


CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES

**HEADWORK BUILDING
HVAC ROOF PLAN**


GENERAL LEGEND




GENERAL ELECTRICAL LEGEND



POWER LEGEND



LIGHTING LEGEND (REFER TO LUMINAIRE SCHEDULE FOR PROJECT SPECIFIC LIGHTING FIXTURES)



GENERAL BIDDING CONSTRUCTION NOTES

- THE CONTRACTOR SHALL PROVIDE COMMISSIONING TO ALL SYSTEMS REQUIRED BY NEC AND LOCAL AHJ.
- THE CONTRACTOR SHALL PROVIDE LABOR, MATERIALS AND SUPERVISION NECESSARY TO ACCOMPLISH THE WORK AS SHOWN AND/OR NOTED ON THE DRAWINGS.
- THE ELECTRICAL CONTRACTOR SHALL NOT SCALE DRAWINGS. THE CONTRACTOR SHALL REFER TO THE ARCHITECTURAL PLANS AND ELEVATIONS FOR EXACT LOCATIONS OF ALL EQUIPMENT UNLESS NOTED OTHERWISE.
- ALL WORK PERFORMED SHALL BE DONE BY A LICENSED CONTRACTOR AND IN A FIRST-CLASS WORKMANLIKE MANNER. THE CONTRACTOR SHALL MEET ALL REQUIREMENTS SET FORTH BY ANY LOCAL ORDINANCE AND GOVERNING AUTHORITIES.
- THE CONTRACTOR SHALL PROVIDE ALL REQUIRED INSURANCE FOR PROTECTION AGAINST PUBLIC LIABILITY AND PROPERTY DAMAGE FOR THE DURATION OF THE WORK.
- IT IS NOT THE INTENT OF THE PLANS AND/OR SPECIFICATIONS TO SHOW EVERY MINOR DETAIL OF CONSTRUCTION. THE CONTRACTOR SHALL BE EXPECTED TO FURNISH AND INSTALL ALL ITEMS FOR A COMPLETE ELECTRICAL SYSTEM AND PROVIDE FOR ALL REQUIREMENTS NECESSARY FOR EQUIPMENT TO BE PLACED IN PROPER WORKING ORDER.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR REPAIRING TO ORIGINAL CONDITIONS ANY DAMAGE TO BUILDING SURFACES, EQUIPMENT, ETC CAUSED DURING THE PERFORMANCE OF WORK.
- CORRECTION OF ANY DEFECTS SHALL BE COMPLETED WITHOUT ADDITIONAL CHARGE OR DELAYS AND SHALL INCLUDE REPLACEMENT OR REPAIR OF ANY OTHER PHASE OF THE INSTALLATION WHICH MAY HAVE BEEN CONSEQUENTIALLY DAMAGED.
- LIGHTING MUST MEET WA STATE ENERGY CODE REQUIREMENTS.

SYSTEMS NOT COVERED BY DESIGN SCOPE - CONTRACTOR'S RESPONSIBILITY:

- ALL DEMO AND RESTORING WORK THAT SHALL AFFECT LIFE SAFETY SYSTEMS (FIRE ALARM) SHALL COMPLY WITH NEC 760 AND NFPA 72.

IMPORTANT CODE NOTES

APPLICABLE BUILDING CODES:
 2021 IBC - WA AMENDMENTS
 2023 NEC - WA AMENDMENTS
 2021 IFC WITH WASHINGTON AMENDMENTS
 2021 WSEC

Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE



No.	Revision	Date	By	App'd

Designed: FNG	Scale: N/A
Drawn: WHB	One Inch at Full Scale If Not One Inch Scale Accordingly
Checked:	



Kitsap County Public Works
18 57
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES

ELECTRICAL LEGEND AND GENERAL NOTES

Drawing: E0.00
Sheet: 30 of 47
File: COMPLETE
Date: September 2025

ELECTRICAL ABBREVIATIONS

A	AMPERE	OS	OCCUPANCY SENSOR
AC	ALTERNATING CURRENT, ABOVE COUNTER	PC	PHOTOCELL
AFF	ABOVE FINISHED FLOOR	PNL	PANEL
AIC	AMPERE INTERRUPTING CAPACITY	POC	POINT OF CONNECTION
AL	ALUMINUM	PT	POTENTIAL TRANSFORMER
AMP	AMPERE	PVC	POLYVINYL CHLORIDE
ATS	AUTOMATIC TRANSFER SWITCH	PWR	POWER
AWG	AMERICAN WIRE GAUGE		
BRKR	BREAKER	QTY	QUANTITY
BLDG	BUILDING		
BOH	BACK OF HOUSE	R	EXISTING TO BE REMOVED
C	CONDUIT	RC	REGID CONDUIT
CKT	CIRCUIT	RECEPT	RECEPTACLE
CB	CIRCUIT BREAKER	ROMEX	ELECTRICAL NM CABLE
CCTV	CLOSED CIRCUIT TELEVISION	SD	SMOKE DETECTOR
CLG	CEILING	SER	SERVICE ENTRANCE CABLE
CO	CONDUIT ONLY/CARBON MONOXIDE	SPEC	SPECIFICATIONS
COMM	COMMUNICATIONS	SSBJ	SUPPLY SIDE BONDING JUMPER
CPLC	CONTROL PANEL LIGHTING CONTROL	SW	SWITCH
CT	CURRENT TRANSFORMER	SWBD	SWITCHBOARD
CU	COPPER	SWGR	SWITCHGEAR
CW	COOL WHITE		
D/B	DESIGN/BUILD	TEL	TELEPHONE
DCO	DUPLEX CONVENIENCE OUTLET	TJB	TELECOMMUNICATIONS J-BOX
DISP	GARBAGE DISPOSAL	TTB	TELEPHONE TERMINAL BOARD
DN	DOWN	TYP	TYPICAL
DS	DISCONNECT SWITCH	TVSS	TRANSIENT VOLTAGE SURGE SUPPRESSOR
DW	DISHWASHER	UL	UNDERWRITERS LABORATORIES
		UG	UNDERGROUND
E	EXISTING TO REMAIN	U.O.N.	UNLESS OTHERWISE NOTED
EF	EXHAUST FAN	UTIL	UTILITY
ELEC	ELECTRICAL		
EMT	ELECTRICAL METALLIC TUBING	V	VOLTS
ENT	ELECTRICAL NON-METALLIC TUBING	VD	VOLTAGE DROP
ERRCS	EMERGENCY RADIO RESPONDER COVERAGE SYSTEM	VFD	VARIABLE FREQUENCY DRIVE
EQUIP	EQUIPMENT	VS	VACANCY SENSOR
EXIST	EXISTING		
		W	WATTS
FACP	FIRE ALARM CONTROL PANEL	W/	WITH
FATC	FIRE ALARM TERMINAL CABINET	WCR	WITHSTAND AND CLOSE-IN RATING
F.C.I.O.	FURNISHED BY CONTRACTOR, INSTALLED BY OWNER	WP	WEATHERPROOF
F.O.I.C.	FURNISHED BY OWNER, INSTALLED BY CONTRACTOR	WW	WARM WHITE
FLUOR	FLUORESCENT		
FOH	FRONT OF HOUSE	XFMR	TRANSFORMER
		XFR	TRANSFER IMPEDANCE OR ZONE
GEC	GROUND ELECTRODE CONDUCTOR		
GFCI	GROUND FAULT CIRCUIT INTERRUPTER		
GFP	GROUND FAULT PROTECTION		
GND	GROUND		
GRS	GALVANIZED RIGID STEEL		
HID	HIGH INTENSITY DISCHARGE		
HP	HORSE POWER		
HPWH	HEAT PUMP WATER HEATER		
HT	HEAT TRACE		
HTR	HEATER		
IC	INSULATED CEILING		
IDF	INTERMEDIATE DISTRIBUTION FRAME		
IG	ISOLATED GROUND		
J-BOX/JB	JUNCTION BOX		
JT	JOINT TRENCH		
KCMIL	THOUSAND CIRCULAR MILS		
KEC	KITCHEN EQUIPMENT CONTRACTOR		
KVA	KILOVOLT AMPERES		
KW	KILOWATT		
LOTO	LOCK-OUT-TAG-OUT		
LTG	LIGHTING		
MATV	MASTER ANTENNA TELEVISION		
MBJ	MAIN BONDING JUMPER		
MCA	MINIMUM CIRCUIT AMPACITY		
MCC	MOTOR CONTROL CENTER		
MDP	MAIN DISTRIBUTION PANEL		
MFR	MANUFACTURER		
MIN	MINIMUM		
MLO	MAIN LUGS ONLY		
MOP	MAXIMUM OVERCURRENT PROTECTION		
MPOE	MAIN POINT OF ENTRY		
MTD	MOUNTED		
N	NEUTRAL		
NIC	NOT IN CONTRACT		
NEC	NATIONAL ELECTRICAL CODE (NFPA-70)		
NEMA	NATIONAL ELECTRICAL MANUFACTURER'S ASSOCIATION		
N.T.S.	NOT TO SCALE		
OC	ON CENTER		
OH	OVERHEAD		





GENERAL NOTES


1. THE CONTRACTOR SHALL KEEP POWER INTERRUPTIONS TO A MINIMUM. POWER INTERRUPTIONS SHALL BE OUTSIDE WORKING HOURS.
2. THE CONTRACTOR SHALL INSTALL ALL ELECTRICAL EQUIPMENT, CONDUIT AND WIRE PRIOR TO DEMOLISHING ANY EXISTING SYSTEMS. CONTRACTOR SHALL MINIMIZE INDIVIDUAL EQUIPMENT POWER INTERRUPTIONS BY TRANSFERRING THE EQUIPMENT FROM THE OLD TO THE NEWLY INSTALLED SYSTEMS.
3. THE CONTRACTOR SHALL PERFORM THE WORK AND MAINTAIN PANEL A&B AND ALL THEIR RELATED CABLES/CIRCUIT BREAKERS NOT REPLACED.
4. ADD PLACARD NEXT TO PNL D INDICATING THE LOCATION OF ALL DISCONNECTING MEANS TO DE-ENERGIZE THE BUILDING.

CONSTRUCTION NOTES

► NEW ADDED PANEL.



Call 48 Hours
Before You Dig
1-800-424-5555
UNDERGROUND SERVICE



No.	Revision	Date	By	App'd



Seattle // Spokane // Baltimore
Copyright © FSI consulting engineers

Designed: FNG
Scale: N/A
Drawn: WHB
One Inch at Full Scale
If Not One Inch
Scale Accordingly
Checked:



Kitsap County Public Works
18 57
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPDATES

ONE-LINE DIAGRAM - ADMINISTRATIVE
AND LABORATORY BUILDING

Drawing: E0.02
Sheet: 32 of 47
File: COMPLETE
Date: September 2025


GENERAL NOTES

1. ALL UG CONDUITS SHALL BE SEALED FROM WATER AND MOISTURE.


CONSTRUCTION NOTES

- 1 COUNTY SEWER UTILITY WILL PROVIDE AND INSTALL PLACARD INDICATING THE LOCATION OF THE BUILDING DISCONNECT MEANS WHICH IS THE MAIN CB FOR PANEL 0900 AND THE MAIN CB FOR PANEL D.
- 2 ADD NEW CONDUCTORS FROM THE TRANSFORMER (UPGRADE THE XFMER LUGS IF NO SPACE AVAILABLE) TO NEW PANEL D.
- 3 ADMIN AND LABORATORY BUILDING AREA OF WORK ON THIS DRAWING

MATCH LINE - SEE SHEET E-015



0 20 40
SCALE IN FEET




KEY PLAN

No.	Revision	Date	By	App'd



Seattle // Spokane // Baltimore
Copyright © fsi consulting engineers

Designed: FNG	Scale: N/A
Drawn: WHB	One Inch at Full Scale If Not One Inch Scale Accordingly
Checked:	



Kitsap County Public Works
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPDATES
POWER - SITE LAYOUT - ADMINISTRATIVE
AND LABORATORY BUILDING


Drawing: E0.03
Sheet: 33 of 47
File: COMPLETE
Date: September 2025

DEMOLITION NOTES

- 1) ALL PANELS SHALL REMAIN AS IS. DEMO ONLY CIRCUITS INDICATED AND CONDUITS FROM THE EQUIPMENT TO THE PANELBOARD. DO NOT REMOVE CIRCUIT BREAKERS OR ANY PANEL COMPONENTS.
- 2) DEMO THE ELECTRICAL RELATED TO THE HEAT RECOVERY UNIT.
- 3) DE-ENERGIZE EF-4, EF-2 AND EF-1 (THE EXHAUST FAN FOR THE FUME HOOD AT WEST LAB) UNTIL ALL WORK RELATED TO IT IS FINISHED THEN RESTORE POWER ON SAME CIRCUIT AGAIN.
- 4) DEMO THE ELECTRICAL RELATED TO CU-1, SS-1, CU-3, SS-3 AND AC-1.
- 5) DEMO THE ELECTRICAL RELATED TO THE CABINET HEATERS.
- 6) DEMO THE ELECTRICAL RELATED TO THE CONDENSING UNIT. REFER TO THE MECHANICAL DRAWINGS FOR CONDENSING UNIT SUBJECT TO DEMOLITION.
- 7) DEMO THE ELECTRICAL RELATED TO THE EXHAUST FANS.

GENERAL NOTES

1. RESTORE ELECTRICAL POWER TO EQUIPMENT AFFECTED BY DEMO WORK. RESTORED CONNECTIONS SHALL COMPLY WITH THE CURRENT NEC VERSION.
2. USE FIRE STOP TO FILL THE HOLES AND MAINTAIN THE FIRE RATING OF THE WALLS AFTER DEMOLITION OF PENETRATING CONDUITS.
3. THE ELECTRICAL INSTALLATIONS WITHIN THE DEMOLITION SCOPE SHALL BE REMOVED TOTALLY TO THE PANELBOARD. THE CIRCUIT BREAKERS SHALL REMAIN.
4. PANELBOARD PENETRATIONS SHALL BE SEALED PER NEC REQUIREMENTS.
5. MAINTAIN POWER INTEGRITY TO ALL EQUIPMENT NOT SUBJECT TO DEMOLITION.
6. POWER INTERRUPTION SHALL BE OUTSIDE THE WORKING HOURS OF THE LAB, AND THE INTERRUPTION PERIODS SHALL BE AS MINIMAL AS POSSIBLE AND COORDINATED WITH OPERATIONS PERSONNEL.
7. THE CONTRACTOR SHALL VERIFY AND COORDINATE THE EQUIPMENT TO BE DEMOLISHED WITH THE MECHANICAL SCOPE OF WORK.
8. DEMO AND INSTALL SYSTEMS IN WEST AND EAST LABS IN COMPLIANCE WITH COUNTY-APPROVED LAB CONSTRUCTION PHASING PLAN.



N

1

POWER DEMOLITION - ADMINISTRATION AND LABORATORY BUILDING - LEVEL 1

SCALE: 1/4" = 1'-0"

4 3 2 1 0 4 8 12
SCALE: 1/4" = 1'-0" FEET

No.	Revision	Date	By	App'd



Seattle // Spokane // Baltimore
Copyright © FSI consulting engineers

Designed: FNG

Drawn: WHB

Checked:

Scale:

1/4"

= 1'-0"

One Inch at Full Scale

If Not One Inch

Scale Accordingly




KITSAP COUNTY
ADMINISTRATIVE
18 57
614 Division Street, MS 26
Port Orchard, WA 98366
WASHINGTON

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPDATES

POWER DEMOLITION - ADMINISTRATION AND LABORATORY BUILDING - LEVEL 1

Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE



Drawing: ED1.01

Sheet: 34 of 47

File: COMPLETE

Date: September 2025

GENERAL NOTES


1. REPLACE ANY FLICKERING LIGHTING FIXTURE.
2. REPLACE ALL LIGHTING FIXTURES IN LAB ROOM 101 AND 102.
3. REMOVE THE EXISTING SMOKE DETECTOR IN LAB ROOM 101, AND COORDINATE WITH THE OWNER'S REPRESENTATIVE AND A LICENSED FIRE ALARM SPECIALIST FOR RE-INSTALLING ON THE NEW SUSPENDED CEILING AND ADDING EXTRA DETECTORS INSIDE THE VOID ABOVE THE SUSPENDED CEILING.
4. THE CONTRACTOR SHALL COORDINATE THE LIGHTING FIXTURES' LOCATIONS WITHIN THE MECHANICAL ROOM WITH ALL NEW AND EXISTING ITEMS WITHIN THE SPACE.

CONSTRUCTION NOTES

1) REPLACE THE LIGHTING IN THE MECH. ROOM WHILE KEEPING THE SAME CIRCUIT. COORDINATE THE EXACT LOCATION OF THE LIGHTING FIXTURES WITH THE COUNTY PRIOR TO CONSTRUCTION.

2) REPLACE THE EXISTING (8) LIGHTING FIXTURES LOCATED AT 12' HIGH ALONG BOTH SIDES OF THE HALLWAY (ROOM #100) WITH 6" BLACK 3,600 LUMEN PHOTOCELL EIKO/WESTPORT SURFACE MOUNTED CYLINDER WALL SCONCES (MODEL CWS6S/36W/8CCT3/UNV/PC/BK OR EQUAL). THE REPLACED LIGHTS SHALL BE CONNECTED ON THE EXISTING CIRCUIT. CONNECT LIGHTS TO NEW PHOTOCELL TO BE LOCATED ON EXTERIOR OF MECHANICAL ROOM.

3) REPLACE THE EXISTING (10) LIGHTING FIXTURES LOCATED 4' HIGH ALONG THE NORTH SIDE OF THE HALLWAY WITH 14" BLACK 1,100 LUMEN SUNLITE LED MODERN WALL SCONCE FIXTURES, 30W, 80 CRI (81481-SU). THE REPLACED LIGHTS SHALL BE CONNECTED ON THE EXISTING CIRCUIT. CONNECT LIGHTS TO NEW PHOTOCELL TO BE LOCATED ON EXTERIOR OF MECHANICAL ROOM.



1 LIGHTING - ADMINISTRATION AND LABORATORY BUILDING - LEVEL 1

SCALE: 1/4" = 1'-0"

4 3 2 1 0 4 8 12
SCALE: 1/4" = 1'-0" FEET


No.	Revision	Date	By	App'd



Seattle // Spokane // Baltimore
Copyright © FSi consulting engineers

Designed: FNG
Drawn: WHB
Checked:

Scale:
1/4" = 1'-0"
One Inch at Full Scale
If Not One Inch
Scale Accordingly




Kitsap County Public Works
18 57
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPDATES
LIGHTING - ADMINISTRATION AND LABORATORY BUILDING - LEVEL 1




Drawing: E2.01
Sheet: 36 of 47
File: COMPLETE
Date: September 2025

Call 48 Hours
Before You Dig
1-800-424-5555
UNDERGROUND SERVICE



ISSUED FOR BID	08/2025	MDW	KED
Revision	Date	By	App'd



Seattle // Spokane // Baltimore
 Copyright © fsi consulting engineers



BHC Consultants, LLC
 1601 Fifth Avenue, Suite 500
 Seattle, Washington 98101
 206.505.3400 (fax)
 www.bhcconsultants.com

Designed: N. Palmatier, P.E.
 Drawn: A. Bradley
 Checked: C. Orchitree, P.E.

Scale:
 1/4" = 1'-0"
 One Inch at Full Scale
 If Not One Inch
 Scale Accordingly





Kitsap County Public Works
 18 57
 KITSAP COUNTY
 WASHINGTON
 614 Division Street, MS 26
 Port Orchard, WA 98366

KITSAP COUNTY SEWER UTILITY (KCU) CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC SYSTEM REPLACEMENT
POWER- PROCESS BUILDING LEVEL 1

Drawing: E3.01
 Sheet: 37 of 47
 File: P23-10865_E3.01
 Date: September 2025

Call 48 Hours
 Before You Dig
 1-800-424-5555
 UNDERGROUND SERVICE





CONSTRUCTION NOTES

- 1 EXTEND EXISTING CIRCUIT. PROVIDE NEW CONDUCTORS FROM HVAC CONTROL PANEL "PNL 7200". IT IS ACCEPTABLE TO REUSE EXISTING CONDUIT AND RACEWAY.
- 2 PROVIDE DUCT MOUNTING KIT OR ADAPTER KIT FOR NEW DEVICE IF REQUIRED.
- 3 PROVIDE 3/4" MINIMUM SIZED CONDUIT WITH 1#12 & 1#12G.
- 4 PROVIDE 3/4" MINIMUM SIZED CONDUIT WITH 2#12.
- 5 PROVIDE 3/4" MINIMUM SIZED CONDUIT WITH 1-2/C#18STP.


POWER - PROCESS BUILDING - LEVEL 2



SCALE: 1/4"=1'-0"

4 3 2 1 0 4 8 12
SCALE: 1/4" = 1'-0"
FEET

ISSUED FOR BID	08/2025	MDW	KED
No.	Revision	Date	By



Seattle // Spokane // Baltimore
Copyright © FSI consulting engineers



BHC Consultants, LLC
1601 Fifth Avenue, Suite 500
Seattle, Washington 98101
206.505.3400 (fax)
www.bhcconsultants.com

Designed: N. Palmatier, P.E.

Drawn: A. Bradley

Checked: C. Orchitree, P.E.

Scale:

1/4" = 1'-0"

One Inch at Full Scale

If Not One Inch
Scale Accordingly



Kitsap County Public Works
18 57 KITSAP COUNTY
WASHINGTON

KITSAP COUNTY SEWER UTILITY (KCU) CENTRAL KITSAP TREATMENT

PLANT (CKTP) HVAC SYSTEM REPLACEMENT

**POWER-
PROCESS BUILDING LEVEL 2**

Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE




06/28/2025

Drawing: E3.02

Sheet: 38 of 47

File: P23-10865_E3.02

Date: September 2025




CONDUIT PENETRATION THRU INTERIOR WALL DETAIL

SCALE: NOT TO SCALE

E2.01 E4.01

Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE



No.	Revision	Date	By	App'd



Seattle // Spokane // Baltimore
Copyright © fsi consulting engineers

Designed: FNG	Scale: NOT TO SCALE
Drawn: WHB	One Inch at Full Scale If Not One Inch Scale Accordingly
Checked:	



Kitsap County Public Works
18 57
614 Division Street, MS 26
Port Orchard, WA 98366

CENTRAL KITSAP TREATMENT PLANT (CKTP) HVAC UPGRADES
ELECTRICAL DETAILS - ADMINISTRATIVE
AND LABORATORY BUILDING

Drawing: E4.01
Sheet: 39 of 47
File: COMPLETE
Date: September 2025

PANELBOARD SCHEDULE

NAME: PANEL A (EXISTING)

VOLTAGE RATING: 120/240 VOLTS, 1 PHASE, 3 WIRE

BUS RATING: 400 AMPS

MAIN BREAKER: 300 AMPS

FEED:

MOUNTING: SURFACE

SPECIAL FEATURES:

PANEL DIM: EXISTING

LOCATION: EAST LAB

FED FROM: PNL 0900

NOTES: EXISTING PANEL - SHOWING ONLY THE CIRCUITS
TO BE DEMOLISHED - NO CALCULATIONS

LOAD TYPE	CIRCUIT DESCRIPTION	VA	CKT	BRKR	L1	L2	BRKR	CKT	VA	CIRCUIT DESCRIPTION	LOAD TYPE
L	LIGHTING - LAB		1	20 / 1	-B-		20 / 1	2		RECEPTACLES LUNCH ROOM & LAB STORAGE	R
L	LIGHTING - LUNCH ROOM		3	20 / 1	-C-		20 / 1	4		RECEPTACLES GENERAL OFFICE	R
L	LIGHTING - OFFICE		5	20 / 1	-B-		20 / 1	6		RECEPTACLES SMALL OFFICES	R
H	HEAT LUNCH ROOM		7	20 / 1	-C-		20 / 1	8		RECEPTACLES LAB NE & S WALLS	R
H	HEAT SMALL OFFICE		9	20 / 1	-B-		20 / 1	10		RECEPTACLES LAB S, W & CENTER	R
	SPACE		11		-C-		20 / 1	12		OVEN	X
X	DI		13	20 / 1	-B-		20 / 1	14		DI SOLENOID	X
X	BOD INCUBATOR & RECEPT. NEW BENCH		15	20 / 1	-C-		20 / 2	16		FURNACE	X
X	BOD INCUBATOR & RECEPT. NEW BENCH		17	20 / 1	-B-			18			X
X	HOT PLATE		19	20 / 2	-C-		20 / 1	20		FAN LUNCH ROOM & FUME HOOD	X
X			21		-B-		20 / 1	22		LAB DISHWASHER	X
H	HEAT PUMP OFFICE (split unit)		23	20 / 2	-C-		80 / 2	24		AUTOCLAVE	X
H			25		-B-			26			X
X	DI PUMP		27	30 / 2	-C-		30 / 2	28		HEAT PUMP LAB EAST (split unit)	H
X			29		-B-			30			H
X	REFREGIRATOR		31	20 / 2	-C-		30 / 2	32		HOT WATER PUMP MECH ROOM	H
X			33		-B-			34			H
H	HEAT PUMP LAB WEST (split unit)		35	20 / 2	-C-		20 / 1	36		HEAT	X
H			37	20 / 2	-B-		20 / 1	38		HVAC POWER AND HVAC CTRL PWR	X
H	AC UND		39	20 / 2	-C-		30 / 1	40		VACUUM PUMP	X
H			41	20 / 2	-B-		20 / 1	42		DI	X

LINE LOADS:

VA(L1)

VA(L2)

TOTAL LOAD:

KVA

AMPS

PANEL A (EXISTING) LOAD CALCULATION:

		CONNECTED VA	METHOD	NEC DEMAND	CALC. VA
TOTAL LIGHTING (L) LOAD:	L		ALL @	125%	
TOTAL RECEPTACLE (R) LOAD:	R		FIRST 10KVA @	100%	
TOTAL MOTOR (M) LOAD:	M		REMAINDER OVER 10KVA	50%	
TOTAL HVAC (H) LOAD:	LM		ALL @	100%	
TOTAL MISCELLANEOUS (X) LOAD:	H		ALL @	100%	
TOTAL VA:	X		ALL @	75%	
AVERAGE AMPS @		VA			VA
VOLTAGE PHASE TO PHASE=		AMPS			AMPS

240

PANELBOARD SCHEDULE

NAME: PANEL B (EXISTING)

VOLTAGE RATING: 120/240 VOLTS, 1 PHASE, 3 WIRE

BUS RATING: 100 AMPS

MAIN BREAKER: 100 AMPS

FEED:

MOUNTING: SURFACE

SPECIAL FEATURES:

PANEL DIM: EXISTING

LOCATION: MECHANICAL ROOM

FED FROM: PNL 0900

NOTES: EXISTING PANEL - SHOWING ONLY THE CIRCUITS
TO BE DEMOLISHED - NO CALCULATIONS

LOAD TYPE	CIRCUIT DESCRIPTION	VA	CKT	BRKR	L1	L2	BRKR	CKT	VA	CIRCUIT DESCRIPTION	LOAD TYPE
	SPARE		A	100 / 2	-C-		B				
			C		-A-		20 / 1	D	500	HEATERS, LIGHTS MAIN GEAR 2940	L
L	LIGHTING DRYING ROOM, MENS LOCKERS	1,600	1	20 / 1	-C-		20 / 1	2	1,800	RECEPTACLES DRYING ROOM, HALL	R
L	LIGHTING RESTROOMS	1,600	3	20 / 1	-C-	-A-	20 / 1	4	1,620	RECEPTACLES RESTROOMS+LAB EXHAUST	R
L	LIGHTING UPPER HALLWAY & PHOTOCELL LGTG	1,800	5	20 / 1	-C-		20 / 1	6	1,620	REC. COAT RM&WOMEN'S LOCKER	R
L	LIGHTING LOWER HALLWAY & ENTRANCE	1,800	7	20 / 1	-C-	-A-	40 / 2	8	1,620	RECEPTACLES MECH ROOM	R
L	LIGHTING MECH ROOM AND WOMEN LOCKER	800	9	20 / 1	-C-			10	1,000	STREET LIGHTING + HALL PLUGS	L
LM	PUMP - HOT WATER CIRCULATION #8	1,150	11	20 / 1	-C-	-A-	40 / 2	12	3,000	HEATER - DUCT	H
M	MOTORIZED DAMPERS (243)	1,500	13	20 / 1	-C-			14	3,000		H
X	DRYER	2,700	15	30 / 2	-C-	-A-	30 / 2	16	2,100	SUPPLY FAN	H
X		2,700	17		-C-		30 / 2	18	2,100		H
X	REFRIGERATOR IN HALL	1,800	19	20 / 1	-C-	-A-	30 / 2	20	2,100	RETURN FAN	H
X	REFRIGERATOR IN HALL	1,800	21	20 / 1	-C-		30 / 2	22	2,100		H
H	LAB/NEXT AIR CONDITIONING	2,700	23	30 / 2	-C-	-A-	30 / 2	24	2,100	LAB/NEXT AIR COND	H
H		2,700	25		-C-		20 / 1	26	1,800	HALLWAY INCUBATOR	X
			27	/ 1	-C-	-A-	/ 1	28			
			29	/ 1	-C-		/ 1	30			
			31	/ 1	-C-	-A-	/ 1	32			
			33	/ 1	-C-		/ 1	34			
			35	/ 1	-C-	-A-	/ 1	36			

LINE LOADS: 22,690 VA(L1) VA(L2)

TOTAL LOAD: 49.01 KVA AMPS

PANEL B (EXISTING) LOAD CALCULATION:

		CONNECTED VA	METHOD	NEC DEMAND	CALC. VA
TOTAL LIGHTING (L) LOAD:	L	9100	ALL @	125%	11375
TOTAL RECEPTACLE (R) LOAD:	R	6660	FIRST 10KVA @	100%	6660
			REMAINDER OVER 10KVA	50%	
TOTAL MOTOR (M) LOAD:	M		ALL @	100%	
TOTAL HVAC (H) LOAD:	LM	1150	125% OF LARGEST	125%	1438
	H	21300	ALL @	100%	21300
TOTAL MISCELLANEOUS (X) LOAD:	X	10800	ALL @	75%	8100
TOTAL VA:		49010 VA			48873 VA
AVERAGE AMPS @		204 AMPS			204 AMPS
VOLTAGE PHASE TO PHASE=					

240

LIGHTING SCHEDULE

SYMBOL	MANUFACTURER	FAMILY	DESCRIPTION	OPTIONS	WATTAGE
L1	COOPER	BAA-FSP-14-42-35-EL14W-IP66	FSP		38.3

EQUIPMENT SCHEDULE

EQUIPMENT ID	VA	VOLTS	OUTLET TYPE	CIRCUIT
CU-05	3801.6	240	DS 25A 2P+N+GND	PNL D (NEW)/1,3
CU-04	3801.6	240	DS 25A 2P+N+GND	PNL D (NEW)/5,7
CU-01	2736	240	DS 25A 2P+N+GND	PNL D (NEW)/25,27
ERV-4	1056	120	DS 25A 2P+GND	PNL D (NEW)/9
ERV-01	1941.6	240	DS 25A 2P+N+GND	PNL D (NEW)/2,4
ERV-01 PRE-HEAT HEATER	5772	240	DS 35A 2P+N+GND	PNL D (NEW)/6,8
ERV-01 HEATING HEATER	2308.8	240	DS 25A 2P+N+GND	PNL D (NEW)/14,16
ERV-02	1941.6	240	DS 25A 2P+N+GND	PNL D (NEW)/30,32
ERV-02 PRE-HEAT HEATER	5772	240	DS 35A 2P+N+GND	PNL D (NEW)/34,36
ERV-02 HEATING HEATER	2308.8	240	DS 25A 2P+N+GND	PNL D (NEW)/38,40
ERV-03	1941.6	240	DS 25A 2P+N+GND	PNL D (NEW)/10,12
ERV-03 HEATING HEATER	5772	240	DS 35A 2P+N+GND	PNL D (NEW)/29,31
FCU-01	720	240	DS 25A 2P+N+GND	PNL D (NEW)/11,13
FCU-02	720	240	DS 25A 2P+N+GND	PNL D (NEW)/15,17

FLAG NOTES

1 NEUTRAL IS ADDED FOR FUTURE REPLACEMENT IF REQUIRED.

v 4.0

PANELBOARD SCHEDULE

NAME: PNL D (NEW)

VOLTAGE RATING: **240Δ/120 VOLTS, 1 PHASE, 3 WIRE**

BUS RATING: **250** AMPS

MAIN BREAKER: **250** AMPS

FEED: (1)(3) 400 MCM + (1) #1/0 GND @ (1) 3-1/2' CONDUIT

MOUNTING: **SURFACE - NEMA 4X**

SPECIAL FEATURES: **DPM + SPD**

LOCATION: **20 X 5.75 X 56 WxDxH**

FED FROM: **TFR 0900**

NOTES:

LOAD TYPE	CIRCUIT DESCRIPTION	VA	CKT	BRKR	L1	L2	BRKR	CKT	VA	CIRCUIT DESCRIPTION	LOAD TYPE	
H	CU-05	1,901	1	20 / 2	-A-	-B-	15 / 2	2	971	ERV-01	H	
H								4	971		H	
H	CU-04	1,901	5	20 / 2	-A-	-B-	35 / 2	6	2,886	ERV-01 PRE-HEAT HEATER	H	
H								8	2,886		H	
H	ERV-4	1,056	9	15 / 1	-A-	-B-	15 / 2	10	971	ERV-03	H	
H	FCU-01	360	11	15 / 2				12	971		H	
H		360	13		-A-	-B-	15 / 2	14	1,154	ERV-01 HEATING HEATER	H	
H	FCU-02	360	15	15 / 2				16	1,154		H	
H		360	17		-A-	-B-	20 / 1	18		SPARE		
	SPARE		19	15 / 1			20 / 1	20		SPARE		
H	ERV-4 DUCT HEATER	1,000	21	15 / 1	-A-	-B-	20 / 2	22		SPARE		
	SPARE		23	15 / 1				24				
H	CU-01	1,368	25	15 / 2	-A-	-B-	20 / 2	26		SPARE		
H		1,368	27					28				
H	ERV-03 HEATING HEATER	2,886	29	35 / 2	-A-	-B-	15 / 2	30	971	ERV-02	H	
H		2,886	31					32	971		H	
H	CU-3	2,040	33	25 / 2	-A-	-B-	35 / 2	34	2,886	ERV-02 PRE-HEAT HEATER	H	
H		2,040	35					36	2,886		H	
	SPARE			37	20 / 1	-A-	-B-	15 / 2	38	1,154	ERV-02 HEATING HEATER	H
	SPARE			39	20 / 1				40	1,154		H

LINE LOADS:

23,864 VA(L1)

21,809 VA(L2)

TOTAL LOAD:

45.67 KVA

190.3 AMPS

PNL D (NEW) LOAD CALCULATION:

TOTAL LIGHTING (L) LOAD:

L

ALL @

125%

TOTAL RECEPTACLE (R) LOAD:

R

FIRST 10KVA @

100%

REMAINDER OVER 10KVA

50%

TOTAL MOTOR (M) LOAD:

M

ALL @

100%

TOTAL HVAC (H) LOAD:

LM

125% OF LARGEST

125%

TOTAL MISCELLANEOUS (X) LOAD:

H

ALL @

100%

45673

45673

TOTAL VA:

45673 VA

45673 VA

AVERAGE AMPS @

190 AMPS

190 AMPS

**Call 48 Hours
Before You Dig**



1-800-424-5555


UNDERGROUND SERVICE



SIGNED
Drawing: **E5.01**
Sheet: 40 of 47
File: COMPLETE
Date: September 2025

GENERAL NOTES

1. REPLACE EXISTING SUB-PANEL WITH NEW SUB-PANEL. PROVIDE NEW SUB-PANEL IN EXISTING ENCLOSURE.
2. EXISTING SUB-PANEL IS 34.25 INCHES BY 34.25 INCHES IN AN APPROXIMATELY 36 INCHES BY 36 INCHES BY 8 INCHES DEEP ENCLOSURE.



NAME PLATE SCHEDULE	
NP1	HVAC CONTROL PANEL PNL 7200
NP2	AHU 7202 ALARMS
NP3	AHU 7211 ALARMS
NP4	F 7207 ALARMS

LEGEND PLATE SCHEDULE	
LP1	SMOKE
LP2	ANTIFREEZE
LP3	DIRTY FILTER

Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE



06/28/2025

ISSUED FOR BID	08/2025	MDW	KED
No.	Revision	Date	By



Seattle // Spokane // Baltimore
Copyright © FSI consulting engineers



BHC Consultants, LLC
1601 Fifth Avenue, Suite 500
Seattle, Washington 98101
206.505.3400 (fax)
www.bhconsultants.com

Designed: N. Palmatier, P.E.	Scale: N/A
Drawn: A. Bradley	One Inch at Full Scale
Checked: C. Orchitree, P.E.	If Not One Inch Scale Accordingly



Kitsap County Public Works
18 57
614 Division Street, MS 26
Port Orchard, WA 98366

KITSAP COUNTY SEWER UTILITY (KCU) CENTRAL KITSAP TREATMENT
PLANT (CKTP) HVAC SYSTEM REPLACEMENT
ELECTRICAL - PROCESS BUILDING
PNL 7200 HVAC CONTROL PANEL
ELEVATION

Drawing: E6.01
Sheet: 41 of 47
File: P23-10865_E6.01
Date: September 2025

CHASIS			
RACK	SLOT	TYPE	DESCRIPTION
1	0	RIO	"1769-ANETR ETHERNET IP REMOTE I/O ADAPTER"
1	1	AO	"1769-OF4CI 4 CHANNEL 4-20MA ANALOG OUTPUT"
1	2	AI	"1769-IF4I 4 CHANNEL 4-20MA ANALOG INPUT"
1	3	AI	"1769-IF4I 4 CHANNEL 4-20MA ANALOG INPUT"
1	0	PS	"1769-PB2 2A 24VDC POWER SUPPLY"
1	4	DO	"1769-OB16 16 CHANNEL 24VDC SOURCE DISCRETE OUTPUT"
1	5	DI	"1769-IQ16 16 CHANNEL 24VDC SINK/SOURCE DISCRETE INPUT"

ANALOG OUTPUT					
RACK	SLOT	CHANNEL	TYPE	DESCRIPTION	RANGE
1	1	0	AO	AHU-7202-DM-2 FACE & BYPASS DAMPER ACTUATOR	MIN - MAX 4 MA - 20 MA
1	1	1	AO	AHU-7211-DM-2 FACE & BYPASS DAMPER ACTUATOR	MIN - MAX 4 MA - 20 MA
1	1	2	AO	SPARE	4 MA - 20 MA
1	1	3	AO	SPARE	4 MA - 20 MA

ANALOG INPUT					
RACK	SLOT	CHANNEL	TYPE	DESCRIPTION	RANGE
1	2	0	AI	"AHU-7202-TS-1 SUPPLY TEMPERATURE"	"20 °F - 120 °F 4 mA - 20 mA"
1	2	1	AI	"AHU-7202-DPT-1 FILTER DIFF. PRESSURE"	"0 IN H2O - 1.25 IN H2O 4 MA - 20 MA"
1	2	2	AI	"AHU-7211-TS-1 SUPPLY TEMPERATURE"	"20 °F - 120 °F 4 MA - 20 MA"
1	2	3	AI	"AHU-7211-DPT-1 FILTER DIFF. PRESSURE"	"0 IN H2O - 1.25 IN H2O 4 MA - 20 MA"
1	2	0	AI	"AHU-7211-WM-1 ROOM TEMPERATURE"	"20 °F - 120 °F 4 MA - 20 MA"
1	2	1	AI	"P-7209-WTS-1 WATER TEMPERATURE"	"0 °F - 250 °F 4 MA - 20 MA"
1	2	2	AI	"P-7209-OAS-1 OUTSIDE AIR TEMPERATURE"	"-58 °F - 120 °F 4 MA - 20 MA"
1	2	3	AI	SPARE	"0 % - 100 % 4 MA - 20 MA"

DISCRETE OUTPUT				
RACK	SLOT	CHANNEL	TYPE	DESCRIPTION
1	4	0	DO	AHU-7202-1CR CALL TO RUN
1	4	1	DO	AHU-7202-5CR DIRTY FILTER PILOT LIGHT
1	4	2	DO	AHU-7211-1CR CALL TO RUN
1	4	3	DO	AHU-7211-5CR DIRTY FILTER PILOT LIGHT
1	4	4	DO	F-7205-1CR CALL TO RUN
1	4	5	DO	F-7207-1CR CALL TO RUN
1	4	6	DO	F-7208-1CR CALL TO RUN
1	4	7	DO	P-7209-1CR CALL TO RUN
1	4	8	DO	FA-CR
1	4	9	DO	SPARE
1	4	10	DO	SPARE
1	4	11	DO	SPARE
1	4	12	DO	SPARE
1	4	13	DO	SPARE
1	4	14	DO	SPARE
1	4	15	DO	SPARE

DISCRETE INPUT				
RACK	SLOT	CHANNEL	TYPE	DESCRIPTION
1	5	0	DI	AHU-7202-2CR READY / HOA IN "AUTO"
1	5	1	DI	AHU-7202-3CR SMOKE DETECTOR
1	5	2	DI	AHU-7202-4CR FREEZE PROTECTION
1	5	3	DI	AHU-7211-2CR READY / HOA IN "AUTO"
1	5	4	DI	AHU-7211-3CR SMOKE DETECTOR
1	5	5	DI	AHU-7211-4CR FREEZE PROTECTION
1	5	6	DI	F-7205-2CR READY / HOA IN "AUTO"
1	5	7	DI	FA-CR FIRE ALARM CONTROL PANEL FAN SHUTDOWN
1	5	8	DI	F-7207-2CR READY / HOA IN "AUTO"
1	5	9	DI	F-7207-3CR SMOKE DETECTOR
1	5	10	DI	F-7208-2CR READY / HOA IN "AUTO"
1	5	11	DI	SPARE
1	5	12	DI	SPARE
1	5	13	DI	SPARE
1	5	14	DI	SPARE
1	5	15	DI	SPARE

Path: S:\Cad\Kitsap County\23-10865 CKTP HVAC System Repl'd Filename: P23-10865_E6.02 Plot date: Aug 28, 2025-04:21:48pm CAD User: Jlira.

	ISSUED FOR BID	08/2025	MDW
No.	Revision	Date	By



Seattle // Spokane // Baltimore
Copyright © FSi consulting engineers



BHC Consultants, LLC
1601 Fifth Avenue, Suite 500
Seattle, Washington 98101

Designed: N. Palmatier, P.E.
Drawn: A. Bradley
Checked: C. Orchiltree, P.E.

Scale:
One Inch
If Not
Scale A

N/A

at Full Scale




One Inch
Accordingly

1

The logo for Kitsap 18, featuring a stylized '18' inside a shield-shaped frame with the word 'KITSAP' at the top and 'WA SH' at the bottom.

The logo for Kitsap 18, featuring a stylized '18' inside a shield-shaped frame with the word 'KITSAP' at the top and 'WA SH' at the bottom.



Kitsap County Public Works


14 Division Street, MS 26
Port Orchard, WA 98366

**KITSAP COUNTY SEWER UTILITY (KCU) CENTRAL KITSAP TREATMENT
PLANT (CKTP) HVAC SYSTEM REPLACEMENT**

**ELECTRICAL - PROCESS BUILDING
PNL 7200 HVAC CONTROL PANEL
I/O LISTING**

Call 48 Hours Before You Dig


 **1-800-424-5555**
UNDERGROUND SERVICE



Drawing: **E6.02**
Sheet: 42 of 47
File: P23-10865_E6.02
Date: September 2025
TANTS, LLC. ALL RIGHTS RESERVED

File: P23-10865_E6.02
Date: September 2025
TANTS, LLC. ALL RIGHTS RESERVED

LLC. ALL RIGHTS RESERVED



GENERAL NOTES

1. CONNECT TO EXISTING POWER CIRCUIT.
2. EXTEND EXISTING CONDUCTORS AND LAND TO NEW TERMINAL BLOCKS.

CONSTRUCTION NOTES

1 PROVIDE TERMINALS AND JUMPER FOR FUTURE FIRE ALARM INTERLOCK.

Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE



Drawing: E7.01
Sheet: 43 of 47
File: P23-10865_E7.01
Date: September 2025

ISSUED FOR BID	08/2025	MDW	KED
No.	Revision	Date	By




Seattle // Spokane // Baltimore
Copyright © fsi consulting engineers



BHC Consultants, LLC
1601 Fifth Avenue, Suite 500
Seattle, Washington 98101
206.505.3400 (voice)
206.505.3406 (fax)
www.bhcconsultants.com



Designed: N. Palmatier, P.E.	Scale: N/A
Drawn: A. Bradley	One Inch at Full Scale
Checked: C. Orchitree, P.E.	If Not One Inch Scale Accordingly



Kitsap County Public Works
18 57
KITSAP COUNTY
WASHINGTON

614 Division Street, MS 26
Port Orchard, WA 98366

KITSAP COUNTY SEWER UTILITY (KCU) CENTRAL KITSAP TREATMENT
PLANT (CKTP) HVAC SYSTEM REPLACEMENT
ELECTRICAL - PROCESS BUILDING
SCHEMATIC WIRING DIAGRAM
1 OF 5



GENERAL NOTES

1. CONNECT TO EXISTING POWER CIRCUIT.
2. EXTEND EXISTING CONDUCTORS AND LAND TO NEW TERMINAL BLOCKS.

Call 48 Hours
Before You Dig



1-800-424-5555
UNDERGROUND SERVICE



Drawing: E7.03
Sheet: 45 of 47
File: P23-10865_E7.03
Date: September 2025

ISSUED FOR BID	08/2025	MDW	KED
No.	Revision	Date	By





GENERAL NOTES


1. CONNECT TO EXISTING POWER CIRCUIT.
2. EXTEND EXISTING CONDUCTORS AND LAND TO NEW TERMINAL BLOCKS.

CONSTRUCTION NOTES

1 PROVIDE TERMINALS AND JUMPER FOR FUTURE FIRE ALARM INTERLOCK.


Call 48 Hours
Before You Dig

1-800-424-5555
UNDERGROUND SERVICE



06/28/2025

ISSUED FOR BID	08/2025	MDW	KED
No.	Revision	Date	By



Seattle // Spokane // Baltimore
Copyright © FSI consulting engineers



BHC Consultants, LLC
1601 Fifth Avenue, Suite 500
Seattle, Washington 98101
206.505.3400 (fax)
www.bhcconsultants.com


Designed: N. Palmatier, P.E.	Scale: N/A
Drawn: A. Bradley	One Inch at Full Scale
Checked: C. Orchitree, P.E.	If Not One Inch Scale Accordingly



Kitsap County Public Works
18 57
KITSAP COUNTY
WASHINGTON
614 Division Street, MS 26
Port Orchard, WA 98366

KITSAP COUNTY SEWER UTILITY (KCU) CENTRAL KITSAP TREATMENT
PLANT (CKTP) HVAC SYSTEM REPLACEMENT
ELECTRICAL - PROCESS BUILDING
SCHEMATIC WIRING DIAGRAM
4 OF 5

Drawing: E7.04
Sheet: 46 of 47
File: P23-10865_E7.04
Date: September 2025



GENERAL NOTES

1. IN WIRING DIAGRAM, THE TAG ID "XX" REFERS TO THE TAG ID ASSOCIATED WITH THE MOTOR.
2. ADAPT WIRING IN EXISTING MCC MOUNTED VFD UNIT. ARRANGE SUCH THAT ON A FIRE ALARM SIGNAL THE VFD WILL STOP OPERATING IN "AUTO" MODE.
3. IT IS ACCEPTABLE TO PROVIDE ADDITIONAL TERMINALS OR USE AVAILABLE TERMINALS.

CONSTRUCTION NOTES


1 ▶ PROVIDE TERMINALS AND JUMPER FOR FUTURE FIRE ALARM INTERLOCK.

Call 48 Hours
 Before You Dig

1-800-424-5555
 UNDERGROUND SERVICE



ISSUED FOR BID	08/2025	MDW	KED
No.	Revision	Date	By



Seattle // Spokane // Baltimore
 Copyright © FSI consulting engineers



BHC Consultants, LLC
 1601 Fifth Avenue, Suite 500
 Seattle, Washington 98101
 206.505.3400 (fax)
 www.bhcconsultants.com

Designed: N. Palmatier, P.E.	Scale: N/A
Drawn: A. Bradley	One Inch at Full Scale
Checked: C. Orchitree, P.E.	If Not One Inch Scale Accordingly



Kitsap County Public Works
 18 57
 KITSAP COUNTY
 614 Division Street, MS 26
 Port Orchard, WA 98366

KITSAP COUNTY SEWER UTILITY (KCU) CENTRAL KITSAP TREATMENT
 PLANT (CKTP) HVAC SYSTEM REPLACEMENT
 ELECTRICAL - PROCESS BUILDING
 SCHEMATIC WIRING DIAGRAM
 5 OF 5

Drawing: E7.05
Sheet: 47 of 47
File: P23-10865_E7.05
Date: September 2025